

Product Data Sheet

May 2010

Black EVA Closed Cell Foam

Grade TF75EVA

Sheet Dimensions: 2000mm x 1000mm x 3, 6, 10, 20mm.

Typical Test Results

Description	Unit	Value	Method
Density	kg/m ³	80	JIS K6767
Tensile Strength	kpa	950	JIS K6767
Elongation	%	150	JIS K6767
Compressive Hardness	kpa	95	JIS K6767
Tear Strength	N/cm	40	JIS K6767
Water Absorption	gm/cm ³	<0.002	JIS K6767
Thermal Conductivity	W/mK	----	ASTMC518
Compression Set	%	4	JIS K6767
Maximum Working Temperature	°C	-60 +60	----

The above data are typical laboratory results only and therefore do not constitute a product specification.

Distributors & Agents for Rubber, Foam & Matting Supplies

- ✓ Self Adhesive Sealing Tape
- ✓ Insertion, Neoprene & Nitrile Rubber
- ✓ Commercial Matting
- ✓ Door & Boot Rubber Seals
- ✓ Grip Products



- ✓ Auto & Marine:
Matting/Carpets/Vinyl
- ✓ Latex & Foam Mattresses
- ✓ Foam Cut to Size
- ✓ Marine Fender & Hatch Seals