## Short shotgun microphone for boom pole and camera mount

- Extremely sharp directivity in a 181.5mm length body
- Though total length only 181.5mm, it has very sharp direction and makes longer reach recording possible
- Only 80g in weight making it easier for operators to work in the field
- Popular in the market due to the compactness and high-quality performance
- Short shotgun mic is ideal for the camcorder mount and boom pole operations

The CS-1e is Sanken's solution to a large demand from many engineers in the video and film Industries. This shotgun mic is easily hidden from the camera's view because of its short length. Although only 181.5mm, the CS-1e has very sharp directivity and provides excellent sound in a wide variety of professional engineering applications.

The CS-1e is very effective on boom poles, and also works extremely well with various kinds of camera mounts for one-man ENG operations. Affordably priced, the CS-1e is ideal for today's highly mobile operators.

## **Common specifications**

Directivity	Super Cardioid / Lobar
Transducer	DC biased condenser
Frequency range	50Hz-20Hz
Sensitivity (nominal at 1kHz)	63.1mV/Pa (-24dB,0dB=1V/Pa)
Equivalent noise level (A-weighted)	15dB-A
Max SPL (1% THD)	130dB SPL
Output impedance at 1KHz	120 ohms
Powering	+48V±4V U.P.F
Current consumption	3.5mA
Weight	80g
Dimensions	181.5mm x 19mm(diameter)
Surface finish	matte black
Connector	XLR-3M

## **Included accessories**

Included Accessories 01	Urethane wind screen
Included Accessories 02	Measurement data
Included Accessories 03	Instruction manual
Included Accessories 04	Warranty card
Included Accessories 05	Vinyl case