

Long distance shotgun pickup with a rich, natural tone

- **120mm long acoustic tube in a standard 250mm length/19mm diameter body**
- **Proprietary Sanken rectangular capsule for super-sharp directivity**
- **Rich, natural, clear sound**

Greater directivity and extended reach over greater distances. A rich, natural sound makes the CS-2 ideal for a wide range of uses, such as for outdoor location sound, interviews, sports, drama, variety shows, and many more.

The "high boost" switch automatically compensates for the attenuation of high frequencies when the mic is used with a windscreen/windjammer for outdoor use. As a result, the full, natural sound is maintained.

Common specifications

Directivity	Super Cardioid / Lobar
Transducer	DC biased condenser
Frequency range	50Hz-20Hz
Sensitivity (nominal at 1kHz)	63.1mV/Pa (-24dB,0dB=1V/Pa)
Equivalent noise level (A-weighted)	15dB-A
Max SPL (1% THD)	130dB SPL
Switch	High boost switch (+3dB/8kHz)
Output impedance at 1KHz	120 ohms
Powering	+48V±4V phantom
Current consumption	less than 3.5mA
Weight	110g
Dimensions	250mm X 19mm (diameter)
Surface finish	matte black
Connector	XLR-3M

Included accessories

Included Accessories 01	Urethane wind screen
Included Accessories 02	Measurement data
Included Accessories 03	Instruction manual
Included Accessories 04	Warranty card
Included Accessories 05	Vinyl case