



Arched Window Swags II

9233

42" to 54" Wide

(Measuring straight across half circle at widest point)

Three decorative rings or holdbacks can attach these swags, or use the beautiful oval rosette pattern included. Attach a full side panel under the swags or use a privacy curtain with the stylish "Flared Pleats." A pattern guide for the pleats and full instructions are included.

Fabric Suggestions: Soft, lightweight fabrics work best. Pleat stack up will be more difficult with thick bulky fabrics. Side swags are always cut on the upright grain. Top swags can be cut upright or bias. Not recommended for fabrics with a nap. Swags and side drapery should line with a regular drapery lining.

YARDAGE

With so many different fabric widths and repeats available today, we find it works best if we give you the actual pattern sizes so you can determine how they will fit on your fabric.

Everything should be cut as pairs. You will need two cuts to make a pair.

TOP CENTER SWAGS

Upright Cut

Bias Cut

42" size....the pattern is.....27" wide x 33" deep.....35" wide x 37" deep
 48" size..the pattern is.....29" wide x 33" deep.....36" wide x 37" deep
 54" size..the pattern is.....31" wide x 33" deep.....37" wide x 37" deep

There is very little fabric difference in the various sizes since it is the width (not depth) that is involved.

SIDE SWAGS

Upright Cut Only

42" size.....the pattern is.....28" wide x 25" deep
 48" size.....the pattern is.....28" wide x 28" deep
 54" size.....the pattern is.....28" wide x 31" deep

Same amount of lining will be needed.

Privacy Curtain: Rod should install just under widest part of arch window. Three widths of fabric will be needed. Add 11 1/2" to your desired finished length. For lining add 4 1/2" to the finished length.

Side Panel: Should install just under widest part of arch window. Measure your length to reach the floor and add 11" (this includes an 8" puddle). Two cut lengths will be needed for one pair, plus lining.

Rosettes: 3/8 yard will do two rosettes. If swag fabric is being used, scraps will be enough. Decorative rings or holdbacks can be used instead.

1/2" hook and loop tape: Swags will need 1/2 yard. Side panels will need 1/2 yard.

Yardage for Trims:

Trims must be able to curve.

Each center swag.....32"

Each side swag.....32"