



Kingston Arched Valance

9205

66" to 76" Wide

(Measuring straight across half circle at widest place.)

This valance is gathered, using shirr tape, at the seam behind the horn. Instructions are included to alter the droop area and/or the fullness in the swags. **There are no instructions for alterations to fit window sizes other than those stated.**

For installation, 4 holdbacks are needed. The valance can attach with ties, or use elastic loops.

Fabric Suggestions: Soft fabrics work best. Stay away from extremely bulky fabrics. Stripes and plaids will not hang straight. Light weight fabrics can be interlined. The returns and horns will need a self or contrast lining. The swag sections can have a drapery lining.

YARDAGE

With so many different fabric widths and repeats available today, we find it works best if we give you the actual pattern sizes so you can determine how they will fit your fabric.

Upright cut

66" to 70" Windows

Center swag	(one is needed)	the pattern is 30" wide x 37" deep
Each side swag	(two are needed)	the pattern is 31" wide x 48" deep
Each horn	(four are needed)	the pattern is 15" wide x 17" deep
Each return	(two are needed)	the pattern is 22" wide x 27" deep

72" to 76" Windows

Center swag	(one is needed)	the pattern is 36" wide x 37" deep
Each side swag	(two are needed)	the pattern is 32" wide x 48" deep
Each horn	(four are needed)	the pattern is 15" wide x 17" deep
Each return	(two are needed)	the pattern is 22" wide x 27" deep

Same amount of lining will be needed.

1 3/8 yds of one cord or two cords shirr tape.

Same amount of interlining (optional)

Trim (must be able to curve)

66" to 77" windows	5 3/8 yards
72" to 76" windows	5 5/8 yards

More detail information about yardage and alterations is given inside packet.