


# CAT40 End Mill Holders

**CAT 40**  
Premium  
Balanced  
**30X**  
RPM



- DIN coolant thru the flange at no extra charge
- Traverse ground shank to obtain optimum accuracy
- Meets or exceeds ANSI specifications
- .0002" TIR or better ensures the best possible cutting tool life
- DIN Coolant option - standard
- All Ground Body
- 100% Forged Construction
- Balanced to

## CAT40 END MILL HOLDERS

Taper	Hole Dia. (d)	Gage Length (L)	L1	D	Set Screw	Part No.
CT40	1/8"	2.50"	0.63"	0.75"	8-32	GS531070
CT40	3/16"	2.50"	0.86"	0.79"	10-32	GS531073
CT40	1/4"	2.50"	1.10"	0.79"	1/4-28	GS531002
CT40	5/16"	2.50"	1.26"	0.87"	5/16-24	GS531008
CT40	3/8"	1.38"	1.34"	1.00"	3/8-24	GS531012
CT40	3/8"	2.50"	1.26"	1.00"	3/8-24	GS531014
CT40	3/8"	4.00"	1.26"	1.00"	3/8-24	GS531016
CT40	1/2"	1.75"	1.50"	1.38"	7/16-20	GS531024
CT40	1/2"	2.50"	1.50"	1.38"	7/16-20	GS531026
CT40	1/2"	4.00"	1.50"	1.38"	7/16-20	GS531028
CT40	5/8"	1.75"	1.61"	1.65"	9/16-18	GS531032
CT40	5/8"	3.00"	1.61"	1.65"	9/16-18	GS531034
CT40	5/8"	5.50"	1.61"	1.65"	9/16-18	GS531038
CT40	3/4"	1.75"	1.77"	1.89"	5/8-18	GS531040
CT40	3/4"	3.00"	1.77"	1.75"	5/8-18	GS531042
CT40	3/4"	5.50"	1.77"	1.75"	5/8-18	GS531046
CT40	7/8"	3.50"	2.08"	2.00"	5/8-18	GS531050
CT40	1"	2.00"	2.36"	2.25"	3/4-16	GS531054
CT40	1"	4.00"	2.36"	2.36"	3/4-16	GS531056
CT40	1"	6.00"	2.36"	2.36"	3/4-16	GS531058
CT40	1-1/4"	2.00"	2.28"	2.25"	3/4-16	GS531060
CT40	1-1/4"	4.00"	2.56"	2.48"	3/4-16	GS531062
CT40	1-1/4"	6.00"	2.55"	2.48"	3/4-16	GS531064
CT40	1-1/2"	4.50"	2.55"	2.99"	3/4-16	GS531066