

Drop-In Ceiling Speaker

Drop-In Ceiling Speaker CSD1X2

Bogen's Drop-In Ceiling Speaker is a full-range speaker that allows for fast and simple installation. No accessories or other hardware required for mounting. Just make one simple cut to the ceiling tile and drop the CSD1X2 in place.

NEW!!

Product Features:

- One-piece assembly saves installation time, effort, and cost
- 1' x 2' perforated grille over entire front of speaker
- 8" dual cone speaker with 10-ounce magnet and tweeter
- 5-watt 25/70V transformer
- Frequency response: 110 Hz – 20 kHz
- 5, 2, 1, 1/2, & 1/4 W tap settings; selectable by rotary switch
- Output 96 dBspl (1W @ 1m)
- 100-degree dispersion
- For use with 2' x 4' and 2' x 2' suspended tile ceilings
- Non-reflective white finish blends in with ceiling tiles
- Integral tile support rail



Dimensions	Product Weight
12-7/8" W x 23-3/4" L x 4-3/4" D	10 lb.

Wall Baffle Speakers



WBS8T725, WBS8T725V, WBS8T725BR, WBS8T725BRV, WBS810T725

Bogen offers 8" cone speakers (S86 and S810) pre-assembled into a simulated walnut-finished wooden enclosure with a black grille cloth on front. These wall baffles are handsomely styled and ruggedly built with 3/8" particle board reinforced at the corners. Recessed volume control and terminal strip are available options on the WBS8T725 model.

Product Features:

- 4-watt capacity
- 6 power taps available (4, 2, 1, 1/2, 1/4, 1/8 watts)
- Simulated walnut finish
- Pre-assembled for faster installation
- Works with both 70V and 25V amplifier outputs
- 8" cone speaker for excellent audio quality
- 6 oz. or 10 oz. magnet weights
- Recessed volume control available (V models only)
- Screw terminals available (BR models only)
- Easy wall-mount installation
- Mounting hardware included

Accessories



AT10A
10W Attenuator



AT35A
35W Attenuator

Dimensions
9-1/2" W x 9-1/2" H x 5-1/4" D (3-1/4" D @ bottom)

Model	Magnet Weight	Frequency Response	Sensitivity (4ft./1W)	No. Volume Control	Recessed Volume Control (V)	Screw Terminals (BR)	Shipping Weight (4/carton)
WBS8T725	6 oz.	50 Hz-12 kHz	95 dBspl	●			18 lb. / carton
WBS8T725V					●		
WBS8T725BR						●	
WBS8T725BRV					●	●	
WBS810T725	10 oz.	70 Hz-15 kHz	96 dBspl	●			20 lb. / carton