



Yeastar 4G LTE Module for S-Series VoIP PBX

4G LTE Module provides full voice capabilities, high speed data transmission for S-Series VoIP PBX, supporting 3G/4G network standard, VoLTE*, and powerful SMS features.

❖ Specifications

| Module | 4G LTE Module | | | | |
|------------------|---|--|---|--|---|
| Type | 4G LTE Module-E | 4G LTE Module-A | 4G LTE Module-AU | 4G LTE Module-J | 4G LTE Module-CE |
| Network Type | UMTS (WCDMA) 3G / LTE | | | | |
| Frequency | LTE FDD: B1/B3/B5/B7/B8/B20 LTE TDD: B38/B40/B41 WCDMA: B1/B5/B8 | LTE FDD: B2/B4/B12 WCDMA: B2/B4/B5 | LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28 LTE TDD: B40 WCDMA: B1/B2/B5/B8 | LTE FDD: B1/B3/B8/B18/B19/B26 LTE TDD: B41 WCDMA: B1/B6/B8/B19 | LTE FDD: B1/B3/B8 LTE TDD: B38/B39/B40/B41 WCDMA: B1/B8 |
| SMS | Yes | | | | |
| MMS | No | | | | |
| Voice Call | 3G/4G Voice Call | | | | |
| SIM Card | 3G/4G Standard SIM Card | | | | |
| Data | 3G/4G Data | | | | |
| 3G Data Speed | Max 384 Kbps (DL) / Max 384 Kbps (UL) | | | | |
| LTE Data Speed | LTE-FDD: Max 150 Mbps (DL) / Max 50 Mbps (UL) LTE-TDD: Max 130 Mbps (DL) / Max 35 Mbps (UL) | | | | |
| Module Insertion | S20&S50: Module Slot 1; S100&S300: Module Slot 1, Expansion Board 1 | | | | |
| Call Waiting | No | | | | |
| Call Forward | Yes | | | | |
| RF Cable | Insert on the MAIN T1 of the 4G LTE module. | | | | |
| Antenna | The 4G LTE module can be used with one RF cable and one antenna. (To strengthen signal, 2 RF cables can be installed but 2 antenna ports will also be occupied with the exception of S20.) | | | | |
| Model | S20, S50, S100, S300 (Version 30.4.0.25 or higher) | | | | |

Click [here](#) to check the supported regions and cellular operators.

*Please check with your operator to see if they support VoLTE and about the cost of VoLTE.