

# PV113-16320433-2T0

P D U I E C C 1 3 - I E C C 1 9 1 6 - 0 4 3 2 A C A P T I V E P L U G - B A S I C P D U



## O V E R V I E W

The PV113-16320433-2T0 Basic PDU is supplied with sixteen (16) IEC-320-C13 & four (4) IEC-320-C19 outlets with a 2.8 meter lead and 32A captive plug. The PV113-16320433-2T0 Basic PDU provides reliable rack power distribution.

## E L E C T R I C A L

Output	(16) IEC C13 10A outlets (4) IEC C20 outlets
Input	(1) 32A Single Phase 56 series captive plug
Lead Length	2.8m
Rating Voltage	250VAC 50.60Hz
Max. Current	32A

## P H Y S I C A L

Colour	Black
Mounting	Supplied with two (2) mounting brackets
Dimensions (HxWxD)	830mm x 44.45mm x 45mm
Shipping Dimensions (HxWxD)	1095mm x 90mm x 120mm
Shipping Weight	5kg

## C O M P L I A N C E

Regulatory Approvals	AS/NZS 3000:2007 Electrical Wiring Standards AS/NZS 3820 Electrical Safety Compliance AS/NZS 3760: 2010 Electrical Safety Testing All Associated Cables Approved to AS/NZS 3191
----------------------	--