

Aksel

This contemporary floor is the quintessential cool Scandi sibling of Astrid, one of our most beloved blondes. Like Astrid, Aksel has the look and feel of raw wood with a protective ultra-matte acrylic finish that shields it from daily wear and tear. It's the perfect pick for those desiring a clean-grade white oak that'll stand up to kids, pets, holiday hosting, and even the occasional Lego tower. As a clean-grade floor, it has almost zero visible knots and will build patina over time while still maintaining a modern aesthetic.

PRODUCT DETAILS

Surface Treatment	Ultra matte lacquer
Refining Treatment	Beveled 2-sided, Brushed
Dimensions	5 ⁷ / ₁₆ x 86 ⁵ %"
Weight per Package	51.8 lbs
Area per Package	32.7 sq. ft.
Area per Pallet	1374.3 sq. ft.
Package Info	Package may contain start and stop boards.
Installation Method	Staple Down, Glue Down, Floating

CERTIFICATES













FACTS

Wood Species	European White Oak
Country of Origin	Lithuania
Grading	Andante
Resandable	2 times
Natural/Stained	Stained
Joint	Locking System
Floor Heating	Yes
Wear Layer Material	Hardwood
Wear Layer Thickness	1/6"
Core Material	Spruce
Core Material Thickness	7/16"
Overall Thickness	9/16"

TECHNICAL PROPERTIES

Moisture Content	5%-9%
Minimun Mean Density kg/m³	>=500 kg/m³
Reaction to Fire	Dfl-sl
Formaldehyde Emission	El
Content PCP	NPD
Breaking Strength N/mm²	NPD
Thermal Conductivity	.13 W/(m*K)
Thermal Resistance R-Value	.11 (m2K/W)
CARB2	Compliant
Slipperiness	USRV 91 R11

DESCRIPTIONS & IMAGERY

Wood is a product of nature - each tree has its own structure and individual color combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the color may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.