



# Drift

Imagine walking through a forest as a crisp, evergreen breeze whistles by, stately trees sway and bark catches the light, creating a dappled pattern on the earth. That sense of peace only nature can provide is both calming and invigorating. Drift exudes that same feeling. Like an afternoon walk in the woods, its 5-inch wide white oak construction features subtle, free-flowing movement, as well as one-of-a-kind graining, knots, and an oiled finish, further highlighting its organic beauty. Drift's design isn't just visually appealing, it's an ideal choice for those desiring beautiful, European-built, and eco-friendly floors.

## PRODUCT DETAILS

Surface Treatment	Oil - This floor should be oiled immediately after installation.
Refining Treatment	Beveled 2-sided, Brushed
Dimensions	5 <sup>7</sup> / <sub>16</sub> x 86 <sup>5</sup> / <sub>8</sub> "
Weight per Package	51.8 lbs
Area per Package	32.7 sq. ft.
Area per Pallet	1374.3 sq. ft.
Package Info	Package may contain start and stop boards.
Installation Method	Staple Down, Glue Down, Floating

## FACTS

Wood Species	European White Oak
Country of Origin	Lithuania
Grading	Vivo
Resandable	2 times
Natural/Stained	Stained
Joint	Locking System
Floor Heating	Yes
Wear Layer Material	Hardwood
Wear Layer Thickness	<sup>1</sup> / <sub>8</sub> "
Core Material	Spruce
Core Material Thickness	<sup>7</sup> / <sub>16</sub> "
Overall Thickness	<sup>9</sup> / <sub>16</sub> "

## TECHNICAL PROPERTIES

Moisture Content	5%-9%
Minimum Mean Density kg/m <sup>3</sup>	>=500 kg/m <sup>3</sup>
Reaction to Fire	Dfl-s1
Formaldehyde Emission	E1
Content PCP	NPD
Breaking Strength N/mm <sup>2</sup>	NPD
Thermal Conductivity	.129 W/(m*K)
Thermal Resistance R-Value	.109 (m2K/W)
CARB2	Compliant
Slipperiness	USRV 45 R10

## CERTIFICATES



## DESCRIPTIONS & IMAGERY

Wood is a product of nature — each tree has its own structure and individual color combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the color may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.