



Faye

Denmark is home to a wealth of fairy tales, thanks mostly to world-famous author Hans Christian Andersen. From The Snow Queen to The Little Mermaid, Andersen's tales have sparked imagination and wonder for centuries after their publication. Beginning life in the enchanting forests of Sweden, Faye tells its own story through swirling grain patterns and subtle knots. Its ultra-matte acrylic finish retains the texture of the wood below, creating a connection to nature with every step. A balanced, mid-tone brown hue brings instant warmth and life to any space.

PRODUCT DETAILS

Surface Treatment	Ultra matte lacquer The appearance of the matte surface may vary due to different light sources and angles.
Refining Treatment	Microbeveled 4-sided, Brushed
Dimensions	6 x 78 3/4"
Weight per Package	32.5 lbs
Area per Package	19.5 sq. ft.
Area per Pallet	1054.2 sq. ft.
Package Info	Package may contain start and stop boards.
Installation Method	Staple Down, Glue Down, Floating

CHARACTER DESCRIPTION

All naturally occurring wood color variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

CERTIFICATES



FACTS

Wood Species	European White Oak
Country of Origin	Sweden
Grading	Lively
Resandable	2 times
Natural/Stained	Stained
Joint	Locking System
Floor Heating	Yes
Warranty	25 Years
Wear Layer Material	Hardwood
Wear Layer Thickness	1/8"
Core Material	Pine/Spruce/Alder
Core Material Thickness	1/2"
Overall Thickness	5/8"

DESCRIPTIONS & IMAGERY

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the color of the products. Your product may vary slightly from the images within this literature.

TECHNICAL PROPERTIES

Moisture Content	EN13183 7%±2%
Minimum Mean Density kg/m ³	>500 kg/m ³
Reaction to Fire	EN13501-1 Dfl-s1
Formaldehyde Emission	EN717-1 E1
Content PCP	CEN/TR14823 ≤ 5x10-6n
Breaking Strength N/mm ²	EN1533 NPD
Thermal Conductivity	EN12664 0,14 W/mK
Thermal Resistance R-Value	.11 (m2 K/W)
Biological Durability	EN350-2 Class 1
CARB2	Compliant
Slipperiness	CEN/TS15676 NPD

COLOR CHANGE

Stained product - moderate color change over time.