

Frida

The texture and beauty of natural white oak are brought to the forefront with Frida, an ultra-matte, wide-plank version of our beloved Tivoli. Just like Tivoli's quintessentially Scandinavian appeal, this floor's unstained finish allows the unique qualities of each board to shine through. When it comes to color, its warm undertones, which range from blonde to tan to light brown, make it a universal floor that will complement your home's design for years, no matter how often you rearrange the furniture. It's like the Goldilocks of floors, perfectly crafted to complement a range of aesthetics.

PRODUCT DETAILS

Surface Treatment	Ultra matte lacquer The appearance of the matte surface may vary due to different light sources and angles.
Refining Treatment	Microbeveled 4-sided, Brushed
Dimensions	7 3/8 x 95 1/4"
Weight per Package	48.5 lbs
Area per Package	29.1 sq. ft.
Area per Pallet	1317.5 sq. ft.
Package Info	Package may contain start and stop boards.
Installation Method	Staple Down, Glue Down, Floating

CHARACTER DESCRIPTION

Naturally occurring wood color variations allowed, from light to dark brown. The product includes large sound and black knots and fillings. Knots and fillings may vary in size and numbers.

CERTIFICATES



FACTS

Wood Species	European White Oak
Country of Origin	Sweden
Grading	Lively
Resandable	2 times
Natural/Stained	Natural
Joint	Locking System
Floor Heating	Yes
Warranty	30 Years
Wear Layer Material	Hardwood
Wear Layer Thickness	1/8"
Core Material	Pine/Spruce/Alder
Core Material Thickness	5/8"
Overall Thickness	3/4"

COLOR CHANGE

Some muting of color variation to medium, straw brown.

DESCRIPTIONS & IMAGERY

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the color of the products. Your product may vary slightly from the images within this literature.

TECHNICAL PROPERTIES

Moisture Content	EN13183 7%±2%
Minimum Mean Density kg/m ³	>500 kg/m ³
Reaction to Fire	EN13501-1 Dfl-s1
Formaldehyde Emission	EN717-1 E1
Content PCP	CEN/TRI4823= 5 x 10-6n
Breaking Strength N/mm ²	EN1533 NPD
Thermal Conductivity	EN12664 0.14 W/mK
Thermal Resistance R-Value	.11 (m2K/W)
Biological Durability	EN350-2 Class 1
CARB2	Compliant
Slipperiness	CEN/TSI5676 NPD