



# Little Square

Throughout the northern cities of Scandinavia, nestled blocks away from well-known, bustling main squares, lie quiet, cozy havens for locals and artists alike. These quaint little squares, often lined with cafes and charming shops, are wonderfully grounding and relaxing, just like this white oak floor. A designer's dream, Little Square has few knots and possesses subtle variances in tone from plank to plank.

## PRODUCT DETAILS

Surface Treatment	Matte finish
Refining Treatment	Microbeveled 4-sided, Brushed
Dimensions	5 x 73 ¼"
Weight per Package	28 lbs
Area per Package	17.8 sq. ft.
Area per Pallet	1120.3 sq. ft.
Package Info	Package may contain start and stop boards.
Installation Method	Staple Down, Glue Down, Floating

## CHARACTER DESCRIPTION

Even color with minor variations. Sapwood may occur. Small sized knots in limited numbers allowed.

## COLOR CHANGE

Stained product - noticeable color change over time.

## CERTIFICATES



## FACTS

Wood Species	European White Oak
Country of Origin	Poland
Grading	Lively
Resandable	2 times
Natural/Stained	Stained
Joint	Locking System
Floor Heating	Yes
Warranty	25 Years
Wear Layer Material	Hardwood
Wear Layer Thickness	⅛"
Core Material	Pine/Spruce lamella
Core Material Thickness	¾"
Overall Thickness	½"

## DESCRIPTIONS & IMAGERY

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the color of the products. Your product may vary slightly from the images within this literature.

## TECHNICAL PROPERTIES

Moisture Content	EN13183 7%±2%
Minimum Mean Density kg/m <sup>3</sup>	>500 kg/m <sup>3</sup>
Reaction to Fire	EN13501-1 Dfl-s1
Formaldehyde Emission	EN717-1 E1
Content PCP	CEN/TR14823 ≤ 5x10 <sup>-6</sup> n
Breaking Strength N/mm <sup>2</sup>	EN1533 NPD
Thermal Conductivity	EN12664 0,08 W/mK
Thermal Resistance R-Value	.15 (m2K/W)
Biological Durability	EN350-2 Class 1
CARB2	Compliant
Slipperiness	CEN/TS15676 NPD