



Swell

If you appreciate the rhythm of rising and falling tides or the irregular beauty in crashing waves, Swell is your floor. This engineered hardwood floor is the perfect neutral hue for any home. Evocative of ripples in the water, cathedral graining - a softly arched grain pattern - is found in some boards. Occasional knots dot the surface, providing a grounding connection to the forest.

PRODUCT DETAILS

Surface Treatment	Matte lacquer
Refining Treatment	No bevel
Dimensions	5 ⁷ / ₁₆ x 86 ⁵ / ₈ "
Weight per Package	51.8 lbs
Area per Package	32.7 sq. ft.
Area per Pallet	1374.3 sq. ft.
Package Info	Package may contain start and stop boards.
Installation Method	Staple Down, Glue Down, Floating

FACTS

Wood Species	European White Oak
Country of Origin	Lithuania
Grading	Animoso
Resandable	2 times
Natural/Stained	Stained
Joint	Locking System
Floor Heating	Yes
Wear Layer Material	Hardwood
Wear Layer Thickness	¹ / ₈ "
Core Material	Spruce
Core Material Thickness	⁷ / ₁₆ "
Overall Thickness	⁹ / ₁₆ "

TECHNICAL PROPERTIES

Moisture Content	5%-9%
Minimum Mean Density kg/m ³	>=500 kg/m ³
Reaction to Fire	Cfl-s1
Formaldehyde Emission	E1
Content PCP	NPD
Breaking Strength N/mm ²	NPD
Thermal Conductivity	.13 W/(m*K)
Thermal Resistance R-Value	.11 (m2K/W)
CARB2	Compliant
Slipperiness	USRV 33 R9

CERTIFICATES



DESCRIPTIONS & IMAGERY

Wood is a product of nature — each tree has its own structure and individual color combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the color may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.