



Tivoli

In the charming center of Copenhagen sits Tivoli Gardens, the original inspiration for Disneyland, a mid-century playground where, for generations, tourists and Danish families have mingled to experience the thrill of a whirlwind day at the park. Like its namesake, this floor is quintessentially Scandinavian and timeless while also being incredibly family-friendly. It has no stain at all, just a matte lacquer finish, so the warmth of the tree's pure color shines through but is well-protected from the evidence of living with little ones. The price-point is also just as friendly, and one of our most accessible floors for achieving that classic Scandinavian look.

PRODUCT DETAILS

Surface Treatment	Matte finish
Refining Treatment	Microbeveled 4-sided, Brushed
Dimensions	5 x 73 ¼"
Weight per Package	28 lbs
Area per Package	17.8 sq. ft.
Area per Pallet	1120.3 sq. ft.
Package Info	Package may contain start and stop boards.
Installation Method	Staple Down, Glue Down, Floating

CHARACTER DESCRIPTION

Even color with minor variations. Sapwood may occur. Small sized knots in limited numbers allowed.

COLOR CHANGE

Some muting of color variation to medium, straw brown.

CERTIFICATES



FACTS

Wood Species	European White Oak
Country of Origin	Poland
Grading	Calm
Resandable	2 times
Natural/Stained	Natural
Joint	Locking System
Floor Heating	Yes
Warranty	25 Years
Wear Layer Material	Hardwood
Wear Layer Thickness	⅛"
Core Material	Pine/Spruce lamella
Core Material Thickness	⅜"
Overall Thickness	½"

DESCRIPTIONS & IMAGERY

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the color of the products. Your product may vary slightly from the images within this literature.

TECHNICAL PROPERTIES

Moisture Content	EN13183 7%±2%
Minimum Mean Density kg/m ³	>500 kg/m ³
Reaction to Fire	EN13501-1 Dfl-s1
Formaldehyde Emission	EN717-1 E1
Content PCP	CEN/TRI4823 ≤ 5x10 ⁻⁶ n
Breaking Strength N/mm ²	EN1533 NPD
Thermal Conductivity	EN12664 0,08 W/mK
Thermal Resistance R-Value	.15 (m2K/W)
Biological Durability	EN350-2 Class 1
CARB2	Compliant
Slipperiness	CEN/TS15676 NPD