



# Zig Zag

Timeless, luxe, and highly durable, Zig Zag will bring a grounding warmth to your home, no matter your design style or budget. Walnut has been a favorite of furniture makers since the Renaissance due to its strength, rich brown hue, and undulating graining. Bring a piece of history home with floors crafted from walnut trees grown in Europe. Zig Zag's boldly-hued, 5-inch wide planks will hold up for years (even with pets and kids!) and gently patina over time, bringing out an earthy caramel quality.

## PRODUCT DETAILS

|                     |  |
|---------------------|--|
| Surface Treatment   | Matte finish                               |
| Refining Treatment  | Microbeveled 4-sided                       |
| Dimensions          | 5 7/8 x 71 1/4"                            |
| Weight per Package  | 45.9 lbs                                   |
| Area per Package    | 35.1 sq. ft.                               |
| Area per Pallet     | 1893.7 sq. ft.                             |
| Package Info        | Package may contain start and stop boards. |
| Installation Method | Glue Down, Floating                        |

## CHARACTER DESCRIPTION

Even color with minor variations. Small sized knots in limited numbers allowed.

## COLOR CHANGE

The color matures over time.

## CERTIFICATES



## FACTS

|                         |                |
|-------------------------|----------------|
| Wood Species            | Walnut         |
| Country of Origin       | Poland         |
| Grading                 | Calm           |
| Resandable              | No             |
| Natural/Stained         | Natural        |
| Joint                   | Locking System |
| Floor Heating           | Yes            |
| Warranty                | 15 Years       |
| Wear Layer Material     | Hardwood       |
| Wear Layer Thickness    | 0"             |
| Core Material           | HDF            |
| Core Material Thickness | 1/4"           |
| Overall Thickness       | 1/4"           |

## TECHNICAL PROPERTIES

|  |                        |
|--|------------------------|
| Moisture Content                       | EN13183 7%±2%          |
| Minimum Mean Density kg/m <sup>3</sup> | 800 kg/m <sup>3</sup>  |
| Reaction to Fire                       | EN13501-1 Cfl-s1       |
| Formaldehyde Emission                  | EN717-1 E1             |
| Content PCP                            | CEN/TR14823≤ 5 x 10-6n |
| Breaking Strength N/mm <sup>2</sup>    | EN1533 NPd             |
| Thermal Conductivity                   | EN12664 0.134 W/mK     |
| Thermal Resistance R-Value             | .0533 (m2K/W)          |
| Biological Durability                  | EN350-2 Class 1        |
| CARB2                                  | Compliant              |

## DESCRIPTIONS & IMAGERY

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the color of the products. Your product may vary slightly from the images within this literature.