

KALE SERIES PROFESSIONAL, POWERFUL, VERSATILE

The Sound Town KALE Series powered loudspeakers are equipped with high quality powerful Class D amplifier that provide plenty of power for their premium woofers and titanium horn-loaded high-frequency compression drivers. Three input channels design make it possible for solo performance with single loudspeaker.

Rugged, compact and lightweight plywood enclosure with engraved handles make it perfect for easy moving.

The KALE series is suited for bands, solo performers, Djs, musicians, entertainers, as well as pubs, bars, schools and houses of worships etc.

KALE-208BPW KALE-208WPW





FEATURES

- * Dual 8" powered full range speaker.
- * 2 x 8" LF with 2" voice coil, 1" titanium compression driver.
- * Built-in Class D amplifier
- * 3 Input channels, 2 band EQ for each channel
- * Blue tooth enabled
- * High grade plywood with quality texture coating available in black and white.
- * suited for bands, solo performers, Djs, musicians, entertainers, as well

as pubs, bars, schools and houses of worships etc.

SPECIFICATIONS

MODEL: KALE-208BPW / KALE-208WPW

SYSTEM DATA: FREQUENCY RESPONSE: 60 Hz - 20kHz SENSITIVITY 96 db (Passive)

SPL MAX: 126 db DISPERSION: 120° x 100° (H x V)

LOUDSPEAKER DATA:

CONFIGURATION: Dual 8" powered full range loudspeaker TRANSDUCER: LF: 2 x 8", HF: 1 x 1" compression driver

IMPEDANCE: 8Ω Nominal POWER HANDLING 800W Peak CONNECTORS:

PHYSICAL:

CABINET CONSTRUCTION: High grade 100% birch plywood

MOUNTING: Stand mount on bottom

FINISH: Texture coating (RAL colors available)

GRILL AND RIGGING COMPONENT: Steel with anti-corrosion coat

DIMENSIONS (MM / INCH): 250 W - 260 D - 590 H / 9.8 W - 10.2 D - 23.2 H

WEIGHT: 14.5 kg / 32 lb AMPLIFIER: CLASS D amp. INPUT: 3 Channels:

2 Channel 1/4" (line) / 1/4" & XLR COMBO (MIC) + 1 Channel 1/8" (AUX) / Bluetooth


OUTPUT: XLR loop out

CONTROL: Treble, Bass and Volume for each channel, Master volume

INDICATOR: Power, Signal, Limiter, Bluetooth VOLTAGE: 100V~240V (50~60Hz)

SPL / IMPEDANCE VS FREQ.





www.soundtown.com 2 Email: support@soundtown.com

KALE-110BPW **KALE-110WPW**



FEATURES

- * 10" powered full range speaker.
- * 1 x 10" LF with 2.5" voice coil, 1" titanium compression driver.
- * Built-in Class D amplifier
- * 3 Input channels, 2 band EQ for each channel
- * Blue tooth enabled
- * High grade plywood with quality texture coating available in black and white.
- * suited for bands, solo performers, Djs, musicians, entertainers, as well as pubs, bars, schools and houses of worships etc.

SPECIFICATIONS

MODEL: KALE-110BPW / KALE-110WPW SYSTEM DATA: FREQUENCY RESPONSE: 58 Hz - 20kHz SENSITIVITY 97 db (Passive) SPL MAX: 128 db DISPERSION: 100° x 45° (H x V)

LOUDSPEAKER DATA: TRANSDUCER:

CONFIGURATION: 10" powered full range loudspeaker LF: 1 x 10", HF: 1 x 1" compression driver

IMPEDANCE: 8Ω Nominal POWER HANDLING 800W Peak CONNECTORS:

PHYSICAL:

CABINET CONSTRUCTION: High grade 100% birch plywood MOUNTING:

Stand mount on bottom

FINISH: Texture coating (RAL colors available)

GRILL AND RIGGING COMPONENT: Steel with anti-corrosion coat

DIMENSIONS (MM / INCH): 315 W - 320 D - 465 H / 12.4 W - 12.6 D - 18.3 H

WEIGHT: 15.5 kg / 34.2 lb AMPLIFIER: CLASS D amp. INPUT: 3 Channels:

2 Channel 1/4" (line) / 1/4" & XLR COMBO (MIC) + 1 Channel 1/8" (AUX) / Bluetooth


OUTPUT: XLR loop out

CONTROL: Treble, Bass and Volume for each channel, Master volume

INDICATOR: Power, Signal, Limiter, Bluetooth VOLTAGE: 100V~240V (50~60Hz)

SPL / IMPEDANCE VS FREQ.





KALE-112BPW **KALE-112WPW**



FEATURES

- * 12" powered full range speaker.
- * 1 x 12" LF with 3" voice coil, 1.4" titanium compression driver.
- * Built-in Class D amplifier
- * 3 Input channels, 2 band EQ for each channel
- * Blue tooth enabled
- * High grade plywood with quality texture coating available in black and white.
- * suited for bands, solo performers, Djs, musicians, entertainers, as well as pubs, bars, schools and houses of worships etc.

SPECIFICATIONS

KALE-112BPW / KALE-112WPW MODEL:

SYSTEM DATA: FREQUENCY RESPONSE: 52 Hz - 20kHz SENSITIVITY 98 db (Passive) SPL MAX: 130 db

DISPERSION: 100° x 70° (H x V) LOUDSPEAKER DATA:

CONFIGURATION: 12" powered full range loudspeaker

TRANSDUCER: LF: 1 x 12", HF: 1 x 1.4" compression driver IMPEDANCE: 8Ω Nominal POWER HANDLING 1200W Peak

CONNECTORS: PHYSICAL:

CABINET CONSTRUCTION: High grade 100% birch plywood MOUNTING: Stand mount on bottom

FINISH: Texture coating (RAL colors available) GRILL AND RIGGING COMPONENT: Steel with anti-corrosion coat

DIMENSIONS (MM / INCH): 360 W - 370 D - 565 H / 14.2 W - 14.6 D - 22.2 H

> WEIGHT: 19.5 kg / 43 lb AMPLIFIER: CLASS D amp. INPUT: 3 Channels:


> > 2 Channel 1/4" (line) / 1/4" & XLR COMBO (MIC) + 1 Channel 1/8" (AUX) / Bluetooth


OUTPUT: XLR loop out

CONTROL: Treble, Bass and Volume for each channel, Master volume

INDICATOR: Power, Signal, Limiter, Bluetooth VOLTAGE: 100V~240V (50~60Hz)

SPL / IMPEDANCE VS FREQ.





Connection Diagram

