

**CHUBU CORPORATION** 

www.hatsuyuki.jp

JOYFEC

BBQ-Roaster







### about us

We are a manufacturer and an exporter of Japanese high quality foodservice equipment, established in 1942. At first, Chubu was opened as a foundry iron works facility. Our iron works technology has developed over the years and now it has become the stable foundation for our foodservice equipment. We develop and supply compact, efficient, and durable Japanese machinery to meet the increasing global demand for the commercial equipment market in the foodservice industry. Our clients include hotels, restaurants, fast-food chains, convenience stores and caterers throughout the world. We believe that our high quality equipment will assist and broaden your commercial foodservice businsess.

Top Product Among our many products, the "Hatsuyuki" ice shaver is the most popular.

Future Plans We are confident that we can make further positive contributions to the ever-changing food

preparation business market. We hope that more and more people worldwide will discover our

products and enjoy the services we offer.

Commitment We are dedicated to the advancement of food preparation technology and are committed to making

it available via our highly professional international sales and service network.

### LOCATION

Address 1533-1 Dogamine, Hagasaki, Kuwana, Mie 511-0944, Japan

Phone 81-594-32-1138 Fax: 81-594-32-1139

Email food-intl@chubu-net.co.jp

**Domestic Sales** 

Branch

Tokyo, Sapporo, Osaka, Hiroshima, Fukuoka, Okinawa

### COMPANY INFORMATION (as of 2016)

Capital Japanese Yen 100,000,000

Employee 325

Products Foodservice Equipment Division

Electric and hand-operated Ice shavers, Ice crushers, etc.

Food preparation equipment - Food slicers, Food processors, Peelers, etc.

Cast iron products - Sukiyaki pan, Iron steak plates, etc.

Construction Metal Division

Roof drains, Traps, Manhole covers, Stainless/Iron gratings, Floor hutches, etc.







# PRODUCTS

Ice Shaver " Hatsuyuki "

P03-P08

Smoothie Machine "Cup Blender"

P09

Vegetable Cutter " PRO CHEF "

P10-P1

Iron Ware "TOKIWA"

P12-P13

Kamameshi Rice Cooker

P14

Smokeless BBQ Roaster "JOYTEC" P15-P20

Baumkuchen Baker

P21-P22

### **Hatsuyuki**

# CARTRIDGE ICE SHAVER

Clean, hygienic and easy operation.

Food contacts only the cartridge and rotor parts of the machine, so they are easy to clean.

New shaved ice is available from ice containing fruit juice and dairy products.

New menu items will be up to your imagination.

Using molded ice, one serving of shaved ice stays perfect.





QR code for the movie on YouTube

### Compact Ice Shaving Machine

### MODEL HD12X

#### Specifications

Dimensions: W267 × D354 × H479mm Electrical: 230V 1Ph. 50/60Hz

Rated current: 140/150W Rated time : 8 minutes. Weight: 10kg

Consisting of: Machine body Big Rotor HD12SA Big Cartridge HD12AA



#### **How To Operate**



Put the ice into the cartridge



Insert the cartridge into the body.



Lower the handle to grip the ice.



Prepare a cup and turn on the





HD09CA

Cartridge (90mm dia x 40mm depth)



### **Hatsuyuki**

# RFOCK ICE SHAVERS





- Easy to clean

Shaving table and its holder are molded to one piece so that roughness of the table is

- Stronger Gripping Power to Ice

The crank handle turns counterclockwise, so it helps to make a stronger grip of the ice.

- Eve-catching motion of the falling shaved ice

Customers can see the falling shaved ice under the shaving table.

230V, 1Ph., 50/60Hz. Electrical: Rated consumption power: 230W(50Hz)/205W(60Hz)  $W347 \times D396 \times H600 (+179.5) mm$ Unit dimensions:

Net weight: 17Kgs

Shavings per min: 1.8Kgs(50Hz)/2.2Kgs(60Hz)

Condenser Motor Driving motor: Rated time: Continuous Effective shaving diameter: 200mm dia








Option: Stand









- It has a larger space for the falling shaved ice with two high stand poles.
- The larger shaving diameter accepts bigger block ice.

Electrical: 230V, 1Ph., 50/60Hz. Rated consumption power: 230W (50Hz) / 205W (60Hz) Unit dimensions:  $W349 \times D447 \times H888 (+186) mm$ 

19Kgs Net weight:

Shavings per min: 1.8Kgs (50Hz) /2.2Kgs (60Hz)

Driving motor: Condenser Motor 20 minutes Rated time : Effective shaving diameter: 213mm dia



MODEL **HB600A** 





Enjoy a substantial profit margin from only a small amount of space. Not only is each unit compact (in size), but can be easily installed and very simple to operate.

Hastuyuki's unique blade adjustment control gives you a choice of ice texture. From coarse and grainy to light as fresh as fallen snow. If you're looking for a cool item for a hot profit, check out Hatsuyuki.



Place an ice block on the table. Turn the crank handle so that the prongs hold the



Adjust the texture of the shaved ice.



Switch on. (Adjust the ice texture during operation.)



#### MODEL **HB320A**

### HB320A NEW FUNCTION

#### ICE LIFT-UP DEVICE

The ice remains longer unmelted (3 to 5 mm above the shaving table). It's easy to take out the reduced flat ice from the chamber. Just shift the prongs up and down with the lever under the table.

Electrical: 230V, 1Ph., 50/60Hz.

Unit dimensions:  $\mathrm{W355} \times \mathrm{D402} \times \mathrm{H565} (+195) \mathrm{mm}$ 


Net weight: 20Kgs

Shavings per min: 1.8Kgs (50Hz) /2.2Kgs (60Hz)

Effective shaving diameter: 200mm dia



Block Ice 200mm dia x 160mm high Max.



Ice touches the shaving table.



Ice is lifted above the table by 4 prongs.



#### **MODEL** HF-500E • HF50DC



Electrical: 115V, 1Ph., 50/60Hz.(HF50DC - DC 12V)

Unit dimensions:  $W305 \times D432 \times H635$ mm

W12-23/32" × D17-25/32" × H25-25/64" 68Lbs/31Kgs (HF50DC -71Lbs/32.5Kgs)

4.4Lbs/2.0Kgs Shavings per min: Effective shaving diameter: 218mm dia

Net weight:



#### MODEL **HA-110S**

Electrical: - Manual -

Unit dimensions:  $W399 \times D273 \times H605mm$ 

Net weight: 14.5Kgs Shavings per min: 0.7Kgs Effective shaving diameter: 200mm dia

#### **Hatsuyuki**

# CUBE ICE SHAVERS

Enjoy a substantial profit margin from only a small amount of space. Not only is each unit compact (in size), but can be easily installed and very simple to operate. Hastuyuki's unique blade adjustment control gives you a choice of ice texture. From coarse and grainy to light as fresh as fallen snow. If you're looking for a cool item for a hot profit, check out Hatsuyuki.











Put in ice cubes.

Adjust ice texture.

Switch On. (Adjust the ice texture during operation.)



#### MODEL HC-S32A

Electrical: 220V, 1Ph., 50/60Hz.

115V, 1Ph., 60Hz.

Unit dimensions : W306  $\times$  D402  $\times$  H429mm

Net weight: 15Kgs Ice hopper: 35 pcs.

Shavings per min: 1.4Kgs(50Hz)/1.7Kgs(60Hz)



#### **MODEL HC-77**B

Electrical: 220V, 1Ph, 50/60Hz. 115V, 1Ph., 60Hz.

240V, 1Ph., 50Hz. 110V, 1Ph., 60Hz.

Unit dimensions : W290  $\times$  D360  $\times$  H499mm

17.3Kgs Net weight: Ice hopper: 70~77 pcs.

Shavings per min: 2.5Kgs(50Hz)/3.0Kgs(60Hz), 6.6Lbs(60Hz)









#### **MODEL** HC8EDC•HC-8E

Electrical: (HC8EDC) DC 12V, 22Kgs/47Lbs

(HC-8E) 115V, 1Ph., 60Hz. Unit dimensions :  $W340 \times D390 \times H430$ mm

(HC8EDC) (HC-8E) 52Lbs, 47Lbs/21.3Kgs

W13-5/16" × D15-1/4" × H17"

70 pcs. Ice hopper: Shavings per min: 2.8Kgs/6.0Lbs

Net weight:



#### **MODEL** HC-18C

220V, 1Ph, 50/60Hz. Electrical: Unit dimensions : W230  $\times$  D266  $\times$  H392mm

Net weight: 9Kgs Ice hopper: 18 pcs.

Shavings per min: 1.8Kgs(50Hz)/1.9Kgs(50Hz)

### **Hatsuyuki**

# CUBE ICE SHAVER CRUSHERS

Combination ice shaver / crusher! Easy operation for crushed ice or shaved ice by the front lever. Shaved ice is as soft and fluffy as fallen snow.





Crushed Ice



### **MODEL**

Electrical: 220V. 1Ph. 50/60Hz. Unit dimensions: W306 × D421 × H429mm

16Kgs Net weight: Ice hopper: 35 pcs

Shavings per min: 1.4Kgs(50Hz)/1.7Kgs(60Hz) 8.5Kgs (50Hz) / 10.0Kgs (60Hz) Crushing:



#### MODEL CS-18C

Electrical: 220V. 1Ph. 50/60Hz. Unit dimensions : W230  $\times$  D275  $\times$  H392mm

Net weight: 10Kgs Ice hopper: 18 pcs

Shavings per min: 1.85Kgs(50Hz)/1.9Kgs(60Hz) 5.3Kgs (50Hz) /7.3Kgs (60Hz) Crushing:

# ICE CRUSHERS

Easy ice crusher for soft and alcoholic drinks. Compact and durable equipment at restaurants, bars, and coffee shops.

#### **ELECTRIC**



2 Crushed Ice Textures 20mm /12mm approx. grain

#### MODEL

100V, 1Ph, 50/60Hz. Electrical: Unit dimensions : W210 × D285 × H355mm

5.8Kgs Net weight: Ice hopper: 30 pcs. Crushings per min: 0.8 - 1.5Kgs

#### **ELECTRIC**



3 Crushed Ice Textures 25mm / 20mm /12mm approx, grain

#### MODEL

Electrical: 100V, 1Ph., 50/60Hz. Unit dimensions :  $W254 \times D314 \times H379$ mm

16Kgs Net weight: Ice hopper: 50 pcs. Crushings per min: 1.3 - 4.0Kgs

#### **MANUAL**



Crushed Ice Texture 12mm approx.grain

#### **MODEL**

#### HA-1700

 $W316 \times D260 \times H317mm$ Unit dimensions:

Net weight: 5Kgs

Crusher Capacity Ice hopper: Crushings per min: 0.6kg per minute

# CUP BLENDER

Semi-automatic fresh juice and smoothie-making machine.



This machine blends small ice cubes (nugget or cubelet ice only), fruits, and vegetables into cool, mild juices or smoothies by the cup.

#### MODEL

Electrical: 100V, 1Ph, 50/60Hz. 190/200W

Rated time: 30 minutes

Blade RPM: 20,000 with no load Dimensions : W228  $\times$  D370  $\times$  H586mm

Weight: 18Kgs

Small cup - 11oz(330ml) approx. Capacity:

29 to 44 seconds per cup Large cup - 14oz (420ml) approx.

35 to 50 seconds per cup

Operation: LED touch panel electric control

system - Three programs

accommodate both large and small cups.



Specific Cup / Cup Supporter





Put the ingredients and the mix base into a cup.



Place it in the cup protector, then place the cup protector on the tray of the machine.



Pre-set the program 3 and push the "START" button.



The mahcine stops automatically after the mixing process finishes.



#### PRO CHEF

# EGETABLE

Chubu's electric food preparation equipment performs quality cuttings fast and easy, slicing and processing vegetables into desired pieces without having to wait. They standardize jobs in the kitchen which not only saves working time and labor cost, but also maintains quality. Temporarily hired part-time staff will perform the same quality work possibly even better and faster.



#### Vegetable Chopper



#### MODEL CV-150B

Electrical: 220V, 1Ph, 160/150W  ${\rm Dimensions: W230 \times D272 \times H380mm}$ 

Net weight: 5kgs/unit

Cabbage 2.0-3.6kgs/min Capacity:

Rated time: 30 minutes

#### MODEL CV-220A

100V, 1Ph, 320/350W  $W364 \times D365 \times H470$ mm 19kgs/unit Cabbage 3.0-13.0kgs/min

30 minutes

#### Mini Slicer





#### MODEL SS-250C

220V, 1Ph, 70/80W W320 × D270 × H505mm 7.5kgs/unit Cabbage 1.5kgs/min (2-blade disk 0.8mm thick)

Continuous

#### MODEL

100V, 1Ph, 115/125W W380 × D360 × H550mm 14.5kgs/unit Cabbage 3.6kgs/min (1.2mm thick) Continuous

#### Cabbage Auto Slicer



Electrical: 100V, 1Ph, 75/90W Dimensions : W360 × D380 × H507mm Net weight: 17kgs/unit Capacity: Cabbage 0.9/1.2kgs/min

(0.8mm thick) Rated time: Continuous

#### Negi (Vegetable) Cutter



## **MODEL**

100V, 1Ph, 32/36W W197 × D312 × H330mm 4.1kgs/unit

30 minutes



## **MODEL**

100V. 1Ph. 80W W258 × D437(+125) × H426mm 12kgs/unit

25 minutes

#### Daikon Oroshi-ki (Root Grater)



Just push the root, then grated.



100V. 1Ph. 300/360W W265 × D367 × H405mm 12kgs/unit Grating Daikon 1.2/1.5kgs/min

20 minutes

### **MODEL**

### SS-250C

- Easily cut vegetables into slices evenly with the big inlet opening.

- Many blade disks are available for any slicer, shredder, and grater application.

- Easy to install (Light weight and 220 V)

#### Many applications with a variety of disks






2-PC blade thin slicing disk SS-0.5B (0.5mm thick) SS-0.8B (0.8mm thick) SS-1.2B (1.2mm thick) SS-1.5B (1.5mm thick)

2-PC medium thick slicing disk SS-2.0B (2.0mm thick) SS-2.5B (2.5mm thick)

















Guide/Pusher attachment for grate





Shredder disk SS-C1B (W1.2 × H3.0mm)  $\begin{array}{l} \text{SS-C2B} \left( \text{W1.5} \times \text{H3.0mm} \right) \\ \text{SS-C3B} \left( \text{W2.0} \times \text{H4.0mm} \right) \end{array}$ 

SS-3.0B (3.0mm thick) SS-3.6B (3.6mm thick)


	SS-0.5B	00 000		
	00 0.0D	SS-0.8B	SS-1.2B	SS-1.5B
Cabbage	1.0kg/min	1.5kg/min	2.25kg/min	3.0kg/min
Potatoes	0.15kg/min	0.25kg/min	0.36kg/min	0.45kg/min
	SS-2.0B	SS-2.5B	SS-3.0B	
Cabbage	3.9kg/min	4.6kg/min	5.6kg/min	
Potatoes	0.6kg/min	0.75kg/min	0.9kg/min	
Lemons	3.0kg/min	4.0kg/min	6.0kg/min	
	SS-C1B	SS-C2B	SS-C3B	
Carrots	0.3kg/min	0.6kg/min	1.2kg/min	4
			SS-D1B	(
Large White Root Radish (Daikon)			2.0kg/min	1

Processing Capacities by Disk:

Remarks : The above is test data based on the following

- products: Cabbage: 1.5kg per pc. Potatoes: 0.2kg per pc. Lemons: 0.15kg per pc. Carrots: 0.2kg per pc. White large root radish (Daikon): 1.0kg per pc.

#### Dimensions of inlet









product at the inlet and push it slowly using the pushing

### Easy for Operation!







Large inlet opening for product.

#### MODEL

The CV-150B is a vertical food chopper especially for vegetables.

Turn on the switch and put in the vegetables (which are already cut into about 4-8 cm without hard core). You will get fine, chopped vegetables immediately from the food outlet. It's the ideal machine for cabbages, onions carrots, etc.

\*As for hard vegetables like carrots, cut them into smaller pieces in advance. Otherwise, they may get caught in the blade and not be chopped properly.

#### HOW TO USE



Turn on the switch and put adequate size vegetables into the slot.



2 Put on the top cover to prevent it from scattering.

Coarseness Adjustment Knob



Chopped vegetables come out from the food outlet automatically.

#### Slot diameter



Just slide the knob and you may select the chopping coarseness of the vegetables.



#### **TOKIWA**

Tokiwa's cast-iron serving plates keep the steaks sizzling long to the last bite.

Grill the meat in the oven or on the griddle first. Then put the steak on the Tokiwa plate for serving to the guest.

The sizzling steak stays delicious and brings the conversation warm at the dining table.

匠の技を受け継ぐ伝統の





In 1601, Tadakatsu Honda, one of the Tokugawa four heavenly kings, became the first lord of the Kuwana government. With an order by the lord, the people of Kuwana started the production of ironware. In 1887, during the Meiji era, high quality sand, which was ideal for cast iron molding, was found in the Kuwana area. This enabled people there to start mass production of cast iron products, which made Kuwana one of the most famous production areas of iron products in Japan. Since that time, people started producing houseware products such as pot lids, furnaces and furnace doors among other iron products. In 1903, manufacturing of cast iron for machinery started in Kuwana, so it became the major place of cast iron production in the western region of Japan.

### STEAK PLATE



NAME: 301 "KOBAN" Size: Small 24cm / Large 30cm

12 pcs per carton (Handle No.707 optional)



NAME: 304 "MARUGATA" Size: Small 17cm

Large 22cm 12 pcs per carton (Handle No.707 optional)



12 pcs per carton (Handle No. 711 optional)




NAME: 306 "FUKAGATA MARU"

Small 15cm Large 20cm 12 pcs per carton

#### Special features of iron ware

Long lasting heat capacity



Made of iron so it's healthy



Food burn and stick resistance



Well balanced radiant heat distribution



#### **OPTION**



707 Handle

711 Handle

### STEAK PAN



NAME: 511 "OIL YAKI KAKU" Size: 25×25cm 25×30cm

5 pcs per carton (Handle No.705 included)





### SUKIYAKI PAN



Size: 16cm 18cm 20cm 22cm

10 pcs per carton



Name: SY11 "TURUTUKI KURO"

Size: 24cm 26cm 28cm 30cm

10 pcs per carton : (24cm & 26cm) 6 pcs per carton : (28cm & 30cm)



NAME: YAMAGA 401

16cm (with Wooden Trivet) 18cm (with Wooden Ladle) 21cm (with Wooden Ladle) 24cm (with Wooden Ladle)

12 pcs per carton: (16cm & 18cm) 6 pcs per carton: (21cm & 24cm)





stand B set



Candle stove set (made with cast iron)



Wooden Trivet



Wooden Ladle



**AUTOMATIC CONTROL WITH MICROCOMPUTER** KAMAMESH RICE COOKE

- Cooking is controlled by a microcomputer. Just put the cooking ingredients into the pot. The unit cooks automatically.
- The key point is to add pressure while cooking, then it cooks in a short time and becomes more delicious.
- A variety of menus are available with the ideal cooking ingredients.

Delicious Kamameshi rice will appeal to young and old alike.

### **MODEL** JKM-10

Model: JKM-10

Unit dimensions: W987  $\times$  D577  $\times$  H360mm AC 100V, 50/60Hz. Electrical:

Consumption power: 150W

Gas connector:

Gas consumption: 17.4kW (15,000kcal/h)

Heating power stove :

High 1,500kcal/h, Low 500kcal/h. LPG 9.5mm dia hose-end or R1/2

13A 13 hose-end or R1/2

Net weight: 50kgs (unit only)

Timer: High Power: Adjustable 1 to 60 minutes

Low Power: Adjustable 1 to 60 minutes Additional Cooking: Adjustable 0 to 6 minutes



### **OPTION** Pressure Lid Kamameshi Set




# KAMAMESHI RICE OKING PO



Outer dimensios :  $16.4 \text{cm} \times 9 \text{cm}$  high Inner dimensions :12.0cm  $\times$  8.7cm deep (Including one wooden coaster, one wooden lid, and one spatula.)

# **OPTION** Pressure Lid



# Duct Type Roasters

We will coordinate your restaurants fashionably.

Three orthodox types will suit your restaurant.

#### Tasty

Can be cooked deliciously.

The best grilling is achieved by making the shape of the gas input burner the ideal design to obtain maximum thermal power.

#### Guard

The unit can be used for a long time.

The stainless steel is adopted to accommodate many parts and the roaster is guarded against corrosion.

#### lean

Easy cleaning.

Clean up is hard work for restaurant workers. Minimizing the numbers of internal parts allows for easy removal and cleaning. The newly designed shape of each part allows for easy cleaning.

#### Vide

Can be widely used.

The flat top-ring and table are flat and widely usable.

#### Safety


The flame rod method for the flame storage device. It is the first among the industry!

The main flame is detected, and unnecessary flames are detected immediately.






#### Safety devices



Piping duct under the floor Exhaust duct Gas/Electrical set-up from the

#### Piping duct over the floor





dimminute.

dimminimini







Grilling mesh

Pilot light ignition

Three thermal power steps: High-Medium-Low Diameter of grilling mesh: 280mm dia.

Water tank capacity: 1,500cc (Max: 1,900cc)

Required exhaust air volume : 280m<sup>3</sup>/h Required fresh air supply volume: 280m3/h Required resistance air pressure: 160Pa Cooling load: 3.81kW

3.49kW (3,000kcal/h) Gas consumption : City Gas :

> L.P.Gas: 3.49kW (0.25kg/h)

Electrical: 220V, single phase, 50/60Hz. 8W Safety devices : Flame failure safety device

Back-fire protection device

Automatic duct damper shut-off device

#### Charcoal Type (with an igniting gas burner)









Pilot light ignition

Three thermal power steps: High-Medium-Low Diameter of grilling mesh: 280mm dia.

Water tank capacity: 1,500cc (Max: 1,900cc)

Required exhaust air volume: 300m<sup>3</sup>/h Required fresh air supply volume: 300m³/h Required resistance air pressure: 180Pa 4.12kW Cooling load:

Gas consumption : City Gas : 3.84kW (3,300kcal/h) 3.84kW (0.27kg/h) L.P.Gas:

Electrical: 220V, single phase, 50/60Hz. 16W Safety devices : Flame failure safety device

Back-fire protection device

Automatic duct damper shut-off device

#### Ceramic-made Charcoal Type (with gas burner)









Grilling mesh

Pilot light ignition

High-Medium-Low Three thermal power steps: Diameter of grilling mesh: 280mm dia.

Water tank capacity: 1,500cc (Max: 1,900cc)

Required exhaust air volume: 280m3/h Required fresh air supply volume: 280m<sup>3</sup>/h Required resistance air pressure: 160Pa Cooling load: 3.81kW

3.49kW (3,000kcal/h) Gas consumption : City Gas :

3.49kW (0.25kg/h) L.P.Gas:

220V, single phase, 50/60Hz. 8W Electrical: Safety devices : Flame failure safety device

Back-fire protection device

Automatic duct damper shut-off device



#### **Enamel-Coating Charcoal Pot Type**

#### CHU

Real charcoal with far-infrared radiation cooks meat deliciously.

Charcoal is used for cooking. No gas burner is equipped.

An internal charcoal-blowing fan can adjust the heating power of the charcoal.


The original effect of the tornado allows you to adjust the heating power of the charcoal uniformly.

Easy removal of the internal parts for easy cleaning. Adjustment for the charcoal blowing fan can be easily made with the smooth dial.

Specifications

Diameter of grilling mesh: 280mm dia. Required exhaust air volume: 360m3/h Required fresh air supply volume: 360m3/h Required resistance air pressure: 160Pa 4.19kW Cooing load:

220V, single phase, 50/60Hz. 8W Electrical:



# Charcoal Ignitor

Easy for igniting charcoal!!

10 Kgs. type and

15 Kgs. type are available.

Compact design for space saving, and good capability for adiabatic heat maintenance.

Specifications

Diameter of exhaust pipe connection: 100mm dia.

Dimensions: 10kgs type: W500mm × D580mm × H1263mm (including an angle-basement)

The blowing fan is available as an optional part.




# Ceiling Hoods

#### **MODEL**

#### JUR

#### Dimension of JUR











#### JUM

#### Dimension of JUM









#### Accessories for joytec roasters

Standard accessories



Roasting plate



Gripper for grilling net



Gripper for Roasting plate

Optional parts and utensils



Table Lid



Stove stand



Hard-Carrier for grilling net



Bill-slip shelf



Sukiyaki hot pot

# Non-ducted (ductless) Type Smokeless Roasters


Ductless type and table layout is unnecessary. There is no need to install ducting pipes and exhaust fans for smoke because of the internal systems.


The internal electric oil / mist collector removes smoke, and the other internal odor-collecting filter removes bad smell.

- Rectifying air-flow system
- Our uniquely designed rectifying air-flow system allows for excellent cooking of meats with natural flavors and juices.
- Safety Devices

For safety, in addition to the flame failure safety device and back-fire protection device, a highly efficient oil filter and large capacity water (drain) pan are equipped on the roaster unit.







#### Gas metal heating plate type

#### NIG-M











Three thermal power steps: Water tank capacity:

Pilot light ignition

Required exhaust air volume : Required fresh air supply volume: 280m3/h

Cooling load :

5.73kW Gas consumption : City Gas : City Gas: 3.25kW (2,800kcal/h)

3.25kW (0.23kg/h) I P Gas:

220V, single phase, 50/60Hz. 280W Electrical: Safety devices:

Flame failure safety device

High-Medium-Low

2.800cc

280m3/h

Fan

Back-fire protection device

Breaker

Odor collecting filter  $\times$  2

#### Charcoal type (with gas burner)









Grilling mesh



Pilot light ignition

Three thermal power steps: High-Medium-Low 2.500cc Water tank capacity: Required exhaust air volume : 300m<sup>3</sup>/h Required fresh air supply volume : 300m<sup>3</sup>/h 6.63kW

Cooling load:

Gas consumption : City Gas : 3.95kW (3,400kcal/h) 3.95kW (0.28kg/h) I P Gas:

220V, single phase, 50/60Hz. 300W Electrical:

Safety devices : Flame failure safety device

Back-fire protection device Breaker



#### Instructions for operation



Fill the container of the unit with mixed creamy dough.



Install the rolling pin rod on the unit.



Dip the pin rod into the mixed creamy dough while manipulating the handle.



Shape the dough around the pin rod with a spatula and bake it.



Repeat Steps 3 and 4 to add lavers to the dough.



Hang the pin rod of baked layered dough on a rack.

# BAUMKUCHEN TREE-RING CAKE ONF RO

Demonstrate baking in front of your customers! This machine bakes a single piece of cake 15cm diameters × 38cm length.

With the skill of the craftsman and increasing layers of the baumkuchen, the in-store baking demonstration is eye-catching and appealing. The performance and aroma of fresh baking attracts many customers and will leave an unforgettable impression.



QR code for the movie on YouTube



#### **MODEL**

#### BUE01B

Specifications

Unit dimensions:  $W745(+135) \times D800 \times H895 \text{ mm}$ 

Electrical: 200V, 3Ph, 50/60Hz.

5.4Kw Power consumption: Rated amperage : 15A


(50Hz) 30rpm (60Hz) 36rpm R.P.M.: Effective baking: 180mm dia × 380mm length maximum

Unit net weight: 120Kgs Creamy dough container: 10liters Alarm Timer 1set

Specifications may change without notice.



30 minutes to bake one roll (15cm diameters × 38cm length)



#### Accessories



- BUR02A Rack for BAUMKUCHEN Oven
- BUA35A Rolling Pin Rod (\$\phi\$35mm)
- BUA60A Rolling Pin Rod (\$\phi\$60mm)
- BUASEA Shaping Spatula Board 659-07 Dough Mixing Spatula
- 519-06 Knife For Sponge Cake (33cm length)

Distributor

### **CHUBU CORPORATION**

1533-1 Dogamine, Hagasaki, Kuwana, Mie, 511-0944, Japan.
Phone: 81-594-32-1138 Fax: 81-594-32-1139
E-mail: food-intl@chubu-net.co.jp

http://www.chubu-net.co.jp/overseas/