1 Identification

- · Product identifier
- · Product Name: Systhane
- · Part Number: S-3306
- $\cdot \textbf{\textit{Application of the substance / the mixture}} \ \textit{Certified Reference Material}$
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SPEX CertiPrep, LLC.

203 Norcross Ave, Metuchen,

NJ 08840 USA

- · Information department: product safety department
- · Emergency telephone number:

Emergency Phone Number (24 hours)

CHEMTREC (800-424-9300)

Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

H361 Suspected of damaging fertility or the unborn child.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS05

GHS07

· Hazard-determining components of labeling:

acetone

· Hazard statements

· Signal word Danger

H225 Highly flammable liquid and vapor.

H314 Causes severe skin burns and eye damage.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Product Name: Systhane

(Contd. of page 1)

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous o	ts:	
67-64-1	acetone	99.9%
88671-89-0	myclobutanil	0.1%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Do not give anything to eat or drink - Do not induce vomitting

- · Information for Doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- $\cdot \textit{For safety reasons unsuitable extinguishing agents: } Water \textit{ with full jet}$
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 3)

Product Name: Systhane

(Contd. of page 2)

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
67-64-1 acetone	200 ppm
· PAC-2:	
67-64-1 acetone	3200* ppm
· PAC-3:	
67-64-1 acetone	5700* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- $\cdot \textit{Control parameters}$
- $\cdot \textit{Components with limit values that require monitoring at the workplace:} \\$

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

67-64-1 acetone PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm RFI

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 4)

Product Name: Systhane

· Protection of hands:

(Contd. of page 3)



Protective gloves

 $The \ glove \ material \ has \ to \ be \ impermeable \ and \ resistant \ to \ the \ product/\ the \ substance/\ the \ preparation.$

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical propertie	es established to the control of the				
· General Information					
· Appearance: Form:	Liquid				
Color: · Odor:	According to product specification Characteristic				
· Odour Threshold:	Not applicable.				
· pH-value at 20 °C (68 °F):	<1				
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 55.8-56.6 °C (132.4-133.9 °F)				
· Flash point:	< 0 °C (<32 °F)				
· Flammability (solid, gaseous):	Not applicable.				
· Ignition temperature:	465 °C (869 °F)				
· Decomposition temperature:	Not applicable.				
· Auto igniting:	Product is not selfigniting.				
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.				
· Explosion limits: Lower: Upper:	2.6 Vol % 13 Vol %				
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)				
 Density Relative density Vapor density Evaporation rate 	Not applicable. Not applicable. Not applicable. Not applicable.				
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.				
· Partition coefficient (n-octanol/wat	er): Not applicable.				
· Viscosity: Dynamic: Kinematic:	Not applicable. Not applicable.				
· Solvent content: Organic solvents: VOC content:	99.9 % 0.00 %				
Solids content:	0.0 %				

(Contd. on page 5)

Product Name: Systhane

(Contd. of page 4)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

67-64-1 acetone

Oral LD50 5,800 mg/kg (rat)

Dermal LD50 20,000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

US

Product Name: Systhane

(Contd. of page 5)

13 Disposal considerations

- $\cdot \ Waste \ treatment \ methods$
- · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

4 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN1090
· UN proper shipping name · DOT · ADR · IMDG, IATA	Acetone 1090 Acetone ACETONE
· Transport hazard class(es)	
· DOT	
R AMMUR FICUR	
· Class · Label	3 Flammable liquids 3
· ADR, IMDG, IATA	J
· Class · Label	3 Flammable liquids 3
· Packing group · DOT, ADR, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category	Warning: Flammable liquids 33 F-E,S-D E
· Transport in bulk according to Annex II of MARPO. Code	L73/78 and the IBC Not applicable.
· Transport/Additional information:	
· ADR · Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	IL Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1090 ACETONE, 3, II

Product Name: Systhane

(Contd. of page 6)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 313 (Specific toxic chemical listings):

88671-89-0 myclobutanil

· TSCA (Toxic Substances Control Act):

67-64-1 acetone

· TSCA new (21st Century Act) (Substances not listed)

88671-89-0 myclobutanil

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

88671-89-0 myclobutanil

· Chemicals known to cause developmental toxicity:

88671-89-0 myclobutanil

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

67-64-1 acetone

· TLV (Threshold Limit Value established by ACGIH)

67-64-1 acetone

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS05

GHS07

GHS08

· Signal word Danger

- · Hazard-determining components of labeling:
- acetone
- · Hazard statements

H225 Highly flammable liquid and vapor.

H314 Causes severe skin burns and eye damage.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: product safety department

Safety Data Sheet acc. to OSHA HCS

Printing date 11/15/2018 Reviewed on 11/15/2018

Product Name: Systhane

· Contact:

(Contd. of page 7)

SPEX CertiPrep, LLC.

1-732-549-7144

· Date of preparation / last revision 11/15/2018 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

CAS: Chemical Abstracts Service (division of the America NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic VPWB: very Persistent and very Bioaccumulative MIOSH: National Institute for Occupational Software

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Skin Corr. IA: Skin corrosion/irritation – Category IA

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3