1 Identification

- · Product identifier
- · Product Name: Stock VOA
- · Part Number: USP-RS-C3A
- · Application of the substance / the mixture Certified Reference Material
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier:
 SPEX CertiPrep, LLC.
 203 Norcross Ave, Metuchen,
 NJ 08840 USA
- Information department: product safety department • Emergency telephone number: Emergency Phone Number (24 hours) CHEMTREC (800-424-9300) Outside US: 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation.

· Label elements

· Hazard pictograms

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- GHS07 GHS08
- · Signal word Danger
- · Hazard-determining components of labeling:
- ethanol
- Hazard statements Causes skin irritation.
- *Causes serious eye irritation. May cause cancer.*
- · Precautionary statements
- Wear protective gloves.

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



(Contd. on page 2)

US

Reviewed on 11/24/2015

Printing date 11/24/2015

Product Name: Stock VOA

Reviewed on 11/24/2015

· HMIS-ratings ((scale 0 - 4)
------------------	---------------

HEALTH	1	Health = 1
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

	s components:	
67-68-5	dimethyl sulfoxide	97.6%
108-10-1	4-methylpentan-2-one	0.1%
64-17-5	ethanol	0.1%
142-82-5	heptane	0.1%
98-82-8	isopropylbenzene	0.1%
109-66-0	pentane	0.1%
Chemical	identification of the substance/preparation	
71-36-3	butan-1-ol	0.1%
71-41-0	1-pentanol	0.1%
71-23-8	propan-1-ol	0.1%
78-92-2	butanol	0.1%
78-93-3	butanone	0.1%
78-83-1	2-methylpropan-1-ol	0.1%
67-63-0	propan-2-ol	0.1%
67-64-1	acetone	0.1%
123-86-4	n-butyl acetate	0.1%
60-29-7	diethyl ether	0.1%
141-78-6	ethyl acetate	0.1%
110-19-0	isobutyl acetate	0.1%
108-21-4	isopropyl acetate	0.1%
79-20-9	methyl acetate	0.1%
	Methyl-tert-butyl ether	0.1%
109-60-4	propyl acetate	0.1%
123-51-3	3-methylbutan-1-ol	0.1%
100-66-3	anisole	0.1%
109-94-4	ethyl formate	0.1%

4 First-aid measures

- · Description of first aid measures
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Information for Doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 11/24/2015

Product Name: Stock VOA

· Advice for firefighters

· Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- \cdot Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:
- 67-68-5 dimethyl sulfoxide

WEEL Long-term value: 250 ppm

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- Avoid contact with the eyes and skin.
- · Breathing equipment:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

(Contd. of page 2)

Reviewed on 11/24/2015

Reviewed on 11/24/2015

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 11/24/2015

Product Name: Stock VOA

· Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

General InformationAppearance:LiquidForm:LiquidColor:According to product specificationOdor:CharacteristicOdor:CharacteristicOdor Threshold:Not applicable.• pH-value:Not applicable.• Change in condition Melting point/Melting range:Undetermined. 189 °C (372 °F)• Flash point:95 °C (203 °F)• Flash point:95 °C (203 °F)• Flammability (solid, gaseous):Not applicable.• Ignition temperature:270 °C (518 °F)• Decomposition temperature:Not applicable.• Danger of explosion:Product is not selfigniting.• Danger of explosion:Product os not present an explosion hazard.• Explosion limits: Lower: Upper:1.8 V0 % (Upper:• Vapor pressure at 20 °C (68 °F):2.5 hPa (2 mm Hg)• Density at 20 °C (68 °F) Relative density Vot applicable.1.09332 g/cm³ (9.124 lbs/gal) Not applicable.• Vapor density Vupor density Not applicable.Not applicable.• Vapor density 	
Form:LiquidColor:According to product specificationOdor:CharacteristicOdour Threshold:Not applicable.• pH-value:Not applicable.• Change in condition Metting point/Metling range:INdetermined. 189 °C (372 °F)• Flash point:95 °C (203 °F)• Flash point:95 °C (203 °F)• Flash point:95 °C (203 °F)• Flash point:270 °C (518 °F)• Decomposition temperature:270 °C (518 °F)• Danger of explosion:Product is not selfigniting.• Danger of explosion:Product is not selfigniting.• Vapor pressure at 20 °C (68 °F):2.5 hPa (2 mm Hg)• Density at 20 °C (68 °F)1.09332 g/cm³ (9.124 lbs/gal)• Relative densityNot applicable.• Vapor density	
Color:According to product specification Characteristic Not applicable.Odour Threshold:Not applicable.·pH-value:Not applicable.· PH-value:Not applicable.· Change in condition Melting point/Melting range: Boiling point/Melting range:Undetermined. 189 °C (372 °F)· Flash point:95 °C (203 °F)· Flash point:95 °C (203 °F)· Flash point:270 °C (518 °F)· Decomposition temperature:Not applicable.· Danger of explosion:Product is not selfigniting.· Danger of explosion:Product does not present an explosion hazard.· Explosion limits: Upper:1.8 Vol % 6.30 Vol %· Vapor pressure at 20 °C (68 °F):2.5 hPa (2 mm Hg)· Density at 20 °C (68 °F):1.09332 g(cm³ (9.124 lbs/gal)) Not applicable.· Vapor density · Vapor andensity · Vapor andensity · Vapor andensity · Vapor andensity · Vapor applicable.Not applicable.	
· Odour Threshold:Not applicable.· pH-value:Not applicable.· Change in condition Melting point/Melting range:Undetermined. 189 °C (372 °F)· Flash point:95 °C (203 °F)· Flash point:95 °C (203 °F)· Flammability (solid, gaseous):Not applicable.· Ignition temperature:270 °C (518 °F)· Decomposition temperature:Not applicable.· Auto igniting:Product is not selfigniting.· Danger of explosion:Product does not present an explosion hazard.· Explosion limits: Upper:1.8 Vol % 63.0 Vol %· Vapor pressure at 20 °C (68 °F):2.5 hPa (2 mm Hg)· Density at 20 °C (68 °F):1.0932 g/cm³ (9.124 lbs/gal) Not applicable.· Vapor density · Vapor densityNot applicable.· Vapor density · Vapor densityNot applicable.· Vapor density · Vapor densityNot applicable.· Vapor density · Evaporation rateNot applicable.	
· pH-value: Not applicable. · Change in condition Melting point/Melting range: Undetermined. 189 °C (372 °F) · Flash point: 95 °C (203 °F) · Flash point: 95 °C (203 °F) · Flammability (solid, gaseous): Not applicable. · Ignition temperature: 270 °C (518 °F) · Decomposition temperature: Not applicable. · Auto igniting: Product is not selfigniting. · Danger of explosion: Product does not present an explosion hazard. · Explosion limits: Lower: 1.8 Vol % (Upper: · Upper: 63.0 Vol % · Vapor pressure at 20 °C (68 °F): 2.5 hPa (2 mm Hg) · Density at 20 °C (68 °F) 1.09332 g/cm³ (9.124 lbs/gal) · Relative density Not applicable. · Vapour density Not applicable. · Vapour density Not applicable.	
• Change in condition Melting point/Melting range: Undetermined. 189 °C (372 °F) • Flash point: 95 °C (203 °F) • Flash point: 95 °C (203 °F) • Flammability (solid, gaseous): Not applicable. • Ignition temperature: 270 °C (518 °F) • Decomposition temperature: Not applicable. • Juito igniting: Product is not selfigniting. • Danger of explosion: Product does not present an explosion hazard. • Explosion limits: 1.8 Vol % Upper: 63.0 Vol % • Vapor pressure at 20 °C (68 °F): 2.5 hPa (2 mm Hg) • Density at 20 °C (68 °F) 1.09332 g/cm³ (9.124 lbs/gal) • Relative density Not applicable. • Vapour density Not applicable. • Vapour density Not applicable.	
Melting point/Melting range:Undetermined. 189 °C (372 °F)· Flash point:95 °C (203 °F)· Flammability (solid, gaseous):Not applicable.· Ignition temperature:270 °C (518 °F)· Decomposition temperature:Not applicable.· Auto igniting:Product is not selfigniting.· Danger of explosion:Product does not present an explosion hazard.· Explosion limits: Lower:1.8 Vol % 63.0 Vol %· Vapor pressure at 20 °C (68 °F):2.5 hPa (2 mm Hg)· Density at 20 °C (68 °F):1.09332 g/cm³ (9.124 lbs/gal) Not applicable.· Not applicable.Not applicable.· Vapour densityNot applicable.	
Boiling point/Boiling range:189 °C (372 °F)· Flash point:95 °C (203 °F)· Flammability (solid, gaseous):Not applicable.· Ignition temperature:270 °C (518 °F)· Decomposition temperature:Not applicable.· Auto igniting:Product is not selfigniting.· Danger of explosion:Product does not present an explosion hazard.· Explosion limits:1.8 Vol %· Upper:63.0 Vol %· Vapor pressure at 20 °C (68 °F):2.5 hPa (2 mm Hg)· Density at 20 °C (68 °F)1.09332 g/cm³ (9.124 lbs/gal)· Relative densityNot applicable.· Vapor atensityNot applicable.	
• Flash point: 95 °C (203 °F) • Flammability (solid, gaseous): Not applicable. • Ignition temperature: 270 °C (518 °F) • Decomposition temperature: Not applicable. • Auto igniting: Product is not selfigniting. • Danger of explosion: Product does not present an explosion hazard. • Explosion limits: 1.8 Vol % Upper: 63.0 Vol % • Vapor pressure at 20 °C (68 °F): 2.5 hPa (2 mm Hg) • Density at 20 °C (68 °F) 1.09332 g/cm³ (9.124 lbs/gal) • Relative density Not applicable. • Vapor density Not applicable. • Vapor at ensity Not applicable. • Vapor density Not applicable.	
• Flammability (solid, gaseous): Not applicable. • Ignition temperature: 270 °C (518 °F) • Decomposition temperature: Not applicable. • Auto igniting: Product is not selfigniting. • Danger of explosion: Product does not present an explosion hazard. • Explosion limits: 1.8 Vol % Lower: 1.8 Vol % Upper: 63.0 Vol % • Vapor pressure at 20 °C (68 °F): 2.5 hPa (2 mm Hg) • Density at 20 °C (68 °F) 1.09332 g/cm³ (9.124 lbs/gal) • Relative density Not applicable. • Vapor density Not applicable. • Vapor atom sity Not applicable.	
Ignition temperature:270 °C (518 °F)Decomposition temperature:Not applicable.Auto igniting:Product is not selfigniting.Danger of explosion:Product does not present an explosion hazard.Explosion limits:Is Vol %Lower:1.8 Vol %Upper:63.0 Vol %Vapor pressure at 20 °C (68 °F):2.5 hPa (2 mm Hg)Density at 20 °C (68 °F)1.09332 g/cm³ (9.124 lbs/gal)Relative densityNot applicable.Vapor utensityNot applicable.Vapor applicable.Not applicable.Vapor applicable.Not applicable.Vapor applicable.Not applicable.Vapor applicable.Not applicable.	
• Decomposition temperature: Not applicable. • Auto igniting: Product is not selfigniting. • Danger of explosion: Product does not present an explosion hazard. • Explosion limits: Image: Second	
• Auto igniting: Product is not selfigniting. • Danger of explosion: Product does not present an explosion hazard. • Explosion limits: Lower: Lower: 1.8 Vol % Upper: 63.0 Vol % • Vapor pressure at 20 °C (68 °F): 2.5 hPa (2 mm Hg) • Density at 20 °C (68 °F) 1.09332 g/cm³ (9.124 lbs/gal) • Relative density Not applicable. • Vapor netsity Not applicable. • Vapor at ensity Not applicable.	
· Danger of explosion: Product does not present an explosion hazard. · Explosion limits: . Lower: 1.8 Vol % Upper: 63.0 Vol % · Vapor pressure at 20 °C (68 °F): 2.5 hPa (2 mm Hg) · Density at 20 °C (68 °F) 1.09332 g/cm³ (9.124 lbs/gal) · Relative density Not applicable. · Vapour density Not applicable. · Evaporation rate Not applicable.	
• Explosion limits: Lower: 1.8 Vol % Upper: 63.0 Vol % • Vapor pressure at 20 °C (68 °F): 2.5 hPa (2 mm Hg) • Density at 20 °C (68 °F) 1.09332 g/cm³ (9.124 lbs/gal) • Relative density Not applicable. • Vapor density Not applicable. • Evaporation rate Not applicable.	
Lower:1.8 Vol %Upper:63.0 Vol %Vapor pressure at 20 °C (68 °F):2.5 hPa (2 mm Hg)Density at 20 °C (68 °F)1.09332 g/cm³ (9.124 lbs/gal)Relative densityNot applicable.Vapour densityNot applicable.Evaporation rateNot applicable.	
Upper:63.0 Vol %· Vapor pressure at 20 °C (68 °F):2.5 hPa (2 mm Hg)· Density at 20 °C (68 °F)1.09332 g/cm³ (9.124 lbs/gal)· Relative densityNot applicable.· Vapour densityNot applicable.· Evaporation rateNot applicable.	
· Vapor pressure at 20 °C (68 °F):2.5 hPa (2 mm Hg)· Density at 20 °C (68 °F)1.09332 g/cm³ (9.124 lbs/gal)· Relative densityNot applicable.· Vapour densityNot applicable.· Evaporation rateNot applicable.	
• Density at 20 °C (68 °F)1.09332 g/cm³ (9.124 lbs/gal)• Relative densityNot applicable.• Vapour densityNot applicable.• Evaporation rateNot applicable.	
• Relative density Not applicable. • Vapour density Not applicable. • Evaporation rate Not applicable.	
Vapour densityNot applicable.Evaporation rateNot applicable.	
• Evaporation rate Not applicable.	
· Solubility in / Miscibility with	
Water: Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not applicable.	
· Viscosity:	7
Dynamic: Not applicable.	
Kinematic: Not applicable.	
· Solvent content:	
Organic solvents: 100.0 %	
<i>VOC content:</i> 99.8 %	
• Other information No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 5)

US

Printing date 11/24/2015

Product Name: Stock VOA

(Contd. of page 4)

Reviewed on 11/24/2015

11 Toxicological information	
• Information on toxicological effects • Acute toxicity:	
LD/LC50 values that are relevant for classification:	
67-68-5 dimethyl sulfoxide	
Oral LD50 14500 mg/kg (rat)	
 on the skin: Irritant to skin and mucous membranes. on the eye: Irritating effect. Sensitization: No sensitizing effects known. Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparatio Irritant Carcinogenic categories 	ons:
· IARC (International Agency for Research on Cancer)	
67-63-0 propan-2-ol	3
108-10-1 4-methylpentan-2-one	28
64-17-5 ethanol	1
98-82-8 isopropylbenzene	28
1634-04-4 Methyl-tert-butyl ether	3
· NTP (National Toxicology Program)	
98-82-8 isopropylbenzene	R
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

• Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

4 Transport information		
· UN-Number · DOT, ADR, IMDG, IATA	Not Regulated	
· UN proper shipping name · DOT, ADR, IMDG, IATA	Not Regulated	
· Transport hazard class(es)		
· DOT, ADR, IMDG, IATA · Class	Not Regulated	
		(Contd. on page 6

Printing date 11/24/2015

Product	Name:	Stock	VOA	

		(Contd. of page 5)
· Packing group · DOT, ADR, IMDG, IATA	Not Regulated	
· Environmental hazards:	Not applicable.	
· Special precautions for user	Not applicable.	
• Transport in bulk according to Annex II of MARPOL73/78 and Code	l the IBC Not applicable.	
· UN "Model Regulation":	Not Regulated	

15 Regulatory information

Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
71-36-3 butan-1-ol	
78-92-2 butanol	
78-93-3 butanone	
67-63-0 propan-2-ol	
108-10-1 4-methylpentan-2-one	
98-82-8 isopropylbenzene	
1634-04-4 Methyl-tert-butyl ether	
TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
Proposition 65	
Chemicals known to cause cancer:	
108-10-1 4-methylpentan-2-one	
98-82-8 isopropylbenzene	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
108-10-1 4-methylpentan-2-one	
64-17-5 ethanol	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
71-36-3 butan-1-ol	D
78-93-3 butanone	Ι
108-10-1 4-methylpentan-2-one	Ι
67-64-1 acetone	I
142-82-5 heptane	D
98-82-8 isopropylbenzene	D, Cl
TLV (Threshold Limit Value established by ACGIH)	
71-23-8 propan-1-ol	2
67-63-0 propan-2-ol	1
67-64-1 acetone	1
64-17-5 ethanol	
1634-04-4 Methyl-tert-butyl ether	2

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 7)

Printing date 11/24/2015

Product Name: Stock VOA

· Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling: ethanol
- · Hazard statements
- Causes skin irritation. Causes serious eye irritation.
- May cause cancer.
- · Precautionary statements
- Wear protective gloves. Wear eye protection / face protection.
- wear eye protection 7 jace protection.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see on this label).

Store locked up.

- Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: product safety department
- · Contact: SPEX CertiPrep, LLC. 1-732-549-7144 · Date of preparation / last revision 11/24/2015 / -· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A Carc. 1A: Carcinogenicity, Hazard Category 1A

(Contd. of page 6)

Reviewed on 11/24/2015