Product Name:	PH-ABT-HC-RFC12
Product Name: Description:	Premier Pharmacy/Vaccine Refrigerator & Freezer Combination 12 Cu. Ft. capacity (10.5 Ref./1.7 Freezer) Two exterior solid swing doors (solid door refrigerator/solid door freezer), right hinged, not reversible Microprocessor temperature controller, refrigerator and freezer Adjustable operating temperature range: Refrigerator: 36°F – 46°F (2°C -8°C); Freezer: 5°F – -13°F (-15°C25°C) Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, "buffered" probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm Audible and visual high and low temperature alarms, refrigerator and freezer Remote alarm contacts, refrigerator and freezer 2 probes; 1 in air and 1 in sample bottle, in both Refrigerator and Freezer Six adjustable shelves with guard rail on back to prevent product from being pushed against back wall, Refrigerator Two adjustable shelves with guard rail on back to prevent product from being pushed against back wall, Freezer Bottom footed shelf to allow air circulation, Refrigerator and Freezer Forced draft circulation Refrigerator Vaccine storage power cord warning label Keyed door locks Magnetic door gasket for positive seal Integrated door handles Leveling legs Stacking kit Two probe access ports (3/8"); one, refrigerator/one, freezer White powder coated exterior HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year
	White powder coated exterior HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs
	Exterior dimensions: 23 5/8" W x 26 1/2" D x 80 1/4" H Manual defrost freezer / cycle defrost refrigerator 115V, 60 Hz, 2.3 Amps refrigerator, 1 Amp freezer, 1/3 HP refrigerator, 1/8 HP freezer UL/C-UL listed Shipping weight: 289 lbs.
	*Please note this unit requires 2 outlets