

Product Name:	PH-ABT-HC-RFC12A
Description:	<p>Premier Pharmacy/Vaccine Refrigerator &amp; Freezer Combination with Auto Defrost Freezer  12 Cu. Ft. capacity (10.5 Ref./1.3 Freezer)  Two exterior solid swing doors (solid door refrigerator/solid door freezer), right hinged, not reversible  Microprocessor temperature controller, refrigerator and freezer  Digital temperature display, refrigerator and freezer  Adjustable operating temperature range: Refrigerator: 36°F – 46°F (2°C -8°C); Freezer: 5°F – -13°F (-15°C - -25°C)  Auto defrost cycle every 6 hours, max air temp in empty freezer: +4.34°C; max air temp in loaded freezer: -2.89°C. Max sample temp in empty freezer: -4.76°C; max sample temp in loaded freezer: -9.58°C.  Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, “buffered” probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual &amp; audible temp alarm  Audible and visual high and low temperature alarms, refrigerator and freezer  2 probes; 1 in air and 1 in sample bottle, in both Refrigerator and Freezer  Remote alarm contacts, refrigerator and freezer  Six adjustable shelves with guard rail on back to prevent product from being pushed against back wall, Refrigerator  Two adjustable shelves with guard rail on back to prevent product from being pushed against back wall, Freezer  Bottom footed shelf to allow air circulation, Refrigerator and Freezer  Forced draft circulation Refrigerator  Vaccine storage power cord warning label  Keyed door locks  Magnetic door gasket for positive seal  Integrated door handles  Leveling legs  Stacking kit  Two probe access ports (3/8"); one, refrigerator/one, freezer  White powder coated exterior  HFC-free refrigerant (R600a), foam insulation and packaging  Pharmacy refrigerator/freezer toolkit and temperature logs  Two year parts and labor warranty, plus an additional three year compressor parts warranty  Exterior dimensions: 23 ¾"W x 26 ½"D x 80 ¼"H  Auto defrost freezer / cycle defrost refrigerator  115V, 60 Hz, 2.3 Amps refrigerator, 1 Amp freezer, 1/3 HP refrigerator, 1/8 HP freezer</p>

UL/C-UL listed

Shipping weight: 289 lbs.

\*Please note this unit requires 2 outlets.

DISCLAIMER: Auto defrost freezers incorporate an electric heater installed on the evaporator that assist in the removal of the frost and ice. Although the heater helps speed up the frost and ice removal, it can raise the temperatures within the freezer.