Latest Revision: 12/31/2020



SDHQ Motorsports 190 S McQueen Rd Ste 109 Gilbert, AZ 85233 Phone: 480-633-2929

Product Packing List

<u> Product: </u>		
Description: 2016+ Tacoma Behind the Grille Light Mount		
(1) Driver Side Bracket	SDHQ-55-1202-G3-A	
(1) Passenger Side Bracket	SDHQ-55-1202-G3-B	
(1) Hardware Package	SDHQ-55-1202-G3-C	
(2) ¼" - 20 x ¾" S.S. Hex Head Bolts		
(2) ¼" - 20 S.S. Lock Nuts		
(2) ¼" S.S. SAE Flat Washers		
(2) ¼" x 1 ¼" S.S. Flat Fender Washers		

Inspected and Packaged By: ______ Date: _____



SDHQ Motorsports 190 S McQueen Rd Ste 109 Gilbert, AZ 85233 Phone: 480-633-2929

INSTALLATION INSTRUCTIONS

Description: 2016+ Tacoma Behind the Grille Light Mount



<u>Parts List</u>	<u>Hardware List</u>	Required Tools
(1) Driver Side Mount SDHQ-55-1202-G3-A (1) Passenger Side Mount SDHQ-55-1202-G3-B (1) Hardware Package SDHQ-55-1202-G3-C	(2) ¼"-20 x ¾" S.S. Hex Head Bolts (2) ¼"-20 S.S. Lock Nuts (2) ¼" S.S. SAE Flat Washers (2) ¼" x 1 ¼" S.S. Flat Fender Washers	10mm Wrench/Socket 7/16" Wrench and Ratchet Appropriate wrenches or sockets to fit your Light Bar


Tech Notes

No Drilling Required

Will Mount most 30" Light Bars in both the upper and lower grill location Some Light Bars may require minor trimming of plastic Optional Add-on: 2016+ Tacoma BTG Dual 10" Light Mount (SDHQ-55-1220-G3)

Approx. Install Time: 1 hour (not including Wiring)

Non-SR5 Grille Options Driver Side Shown






^{***}READ ALL INSTRUCTIONS THOROUGHLY FROM START TO FINISH BEFORE BEGINNING INSTALLATION! ***

Installation Instructions:

- **1.** Unbox all parts and familiarize yourself with them. Verify all parts are present.
- 2. Removing the Grille- Remove the (2) 10mm head screws and (2) clips that attach the top of the grille to the truck.
- 3. Pull up and out on the top mounting ears where you removed the screws to get them free from the plastic inserts under them. Then gently pull the grille off of the front of the truck, the lower section simply pops off, and set the grille aside.



- **4.** Removing the Plastic Shrouds- Remove the panel clip from the side of the shrouds and then pull the shrouds forward, the rear is simply clipped into place. These will not be reused.
- **5.** <u>Installing the Brackets</u>- Remove the outer clip from the top of the bumper on each side.
- **6.** Starting with the driver side, remove the 12mm bolt in the core support that attaches the top of the radiator.
- 7. Insert the driver side bracket with the bracket on top of the sheet metal bumper cover support, but under the bumper cover. Reinsert radiator upper mounting bolt. If SDHQ-55-1220-G3 was purchased, begin those instructions.
- 8. Using supplied 1/4" hardware, attach the bottom of the mount to the sheet metal bumper cover support, with the large fender washer on top of the bumper cover, and then tighten all hardware starting with the top radiator bolt. Repeat Steps 6 8 on the passenger side.









- 9. Mount Lights- Mount your lights in desired locations and wire to manufacture's specifications.
- **10.** Re-install Grille Re-install your grille in the reverse order that it came off. You are complete! Enjoy your new SDHQ Behind the Grille Light Mounts!

Double check all hardware is installed correctly and tight

Re-torque ALL bolts after 100 miles



190 S McQueen Rd Ste 109 Gilbert, AZ 85233

Phone: 480-633-2929 | Fax: 480-633-1791

www.sdhqoffroad.com

Follow us on:



