



KRAMER

CRS-PlugNView-H

Active Optical Armored 4K HDMI Cable



CRSPLUGNVIEWH cable is a highspeed HDMI active optical cable (AOC) designed with heavyduty durability perfectly suited for the harshest use and abuse expected from rental and road applications. CRSPlugNViewH supports resolutions up to 4K@60 (4:4:4) 18 Gbps over long cable runs up to 100 meters without the need for an external power supply or additional extenders

FEATURES

High Resolution over Long Range - Active cable supports resolutions up to 4K@60 (4:4:4) over long cable runs up to 100 meters

High Data Transfer Rate - Up to 18 Gbps

No External Power Needed - Powers the active units via the HDMI connector with a power consumption of only 0.25W:50mA @5V

Comprehensive HDMI Support - HDCP 2.2, HDR10, HLG, Dolby Vision™, deep color, x.v.Color™, 5.1/7.1 lossless Dolby® TrueHD, DTSHD Master Audio®, EDID and CEC

Extremely Durable - integrated. stainless steel, corrugated tube with Kevlar reinforcement protects the internal optical fibers. A TPU jacket, heavy duty connectors and robust waterproof & impact resistant connector covers ensure high pulling strength and compression load. Dispensed from a solid, mobile plastic spool

Varied Selection of Lengths - Available in versions from 10 to 100m (33 to 328ft)



TECHNICAL SPECIFICATIONS

Video	Video Resolution: Up to 4K 60Hz 4:4:4 (3840x2160 & 4096x2160) Data Rate: Up to 18 Gbps Supported color spaces: RGB, YCbCr, xvYCC, Adobe sRGB, sYCC601, BT.2020 HDMI Support: HDCP 2.2, HDR10, HLG, Dolby Vision™, EDID and CEC
Audio	Supported audio formats: Dolby® Digital Plus, Dolby® TrueHD, DTSHD Master Audio®, DVD Audio, SACD
PHYSICAL	Connector-1 (source end): Male HDMI Type A, 24K goldplated Connector-1 (display end): Male HDMI Type A, 24K goldplated HDMI Connector Dimensions: 27.8x 0.78x 0.38 (70.7mm x 20mm x 9.8mm) Cable Structure: Hybrid Optical Fiber Cable Fiber Optic: 50/125u OM3 fiber Armor Material: Kevlar® and stainless steel Long term crush resistance: 1000N (100 kg, 225lbs) Short term crush resistance: 2000N (204 kg, 450lbs) Bending radius: 10 D (Dynamic) / 20 D (Static) Long term tensile strength test: 400N (41 kg, 90lbs) Short term tensile strength test: 800N (81 kg, 180lbs) Connector bending test > 10000 cycles:
JACKET	Material: TPU (thermoplastic polyurethane) LSHF Color: Black Diameter: 5.8mm
Power	Source: No external power supply is needed (draws current from the video source) Consumption 0.25W max.:
Environmental Conditions	Environmental Specification: Operating Temperature: +32~+122F (0~+50C) Storage Temperature: 40~+158F (40~+70C) Operating Humidity: 10 ~ 80%
Regulatory:	
REGULATORY	Environmental: CE, FCC Safety: RoHS 2011/65/ EU
Product Dimensions	24.00cm x 20.00cm x 32.00cm (9.45" x 7.87" x 12.60") W, D, H
Product Weight	5.2kg (11.5lbs) approx
Shipping Dimensions	38.50cm x 26.50cm x 47.00cm (15.16" x 10.43" x 18.50") W, D, H
Shipping Weight	6.3kg (13.9lbs) approx



KRAMER

CONFIGURATIONS

CRS-PlugNView-H-33	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H-50	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H-66	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H-98	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H-131	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H-164	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H-197	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H-230	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H-262	Active Optical Armored 4K HDMI Cable
CRS-PlugNView-H-328	Active Optical Armored 4K HDMI Cable