



TBUS-201xl

Pop-Up Table Mount Multi-Connection
Solution

| VGA/UXGA - 15-pin HD | HDMI | Ethernet - RJ-45



Kramer's TBUS-201xl provides an extremely simple, affordable and elegant single-push pop-up multi-connection boardroom solution. By pressing down gently on the lid, the unit opens and closes pneumatically. TBUS-201xl is fast and easy to install and flexible to configure. It customizes to your own needs and is intuitive to operate

FEATURES

Pneumatic Lift - Easy opening & closing by pressing down gently on the cover. When not in use, it lowers flush with the table

Power Input - Universal, USA, European and many other worldwide power sockets available

4 Fixed Inputs - 15-pin HD, HDMI, 3.5mm & Ethernet

Elegant and Rugged Rectangular Design - The sturdy and attractive anodized aluminum enclosure provides maximum connectivity in the smallest possible footprint, and at the same time is cost effective and easy to install

Installation - Requires tools and expertise to cut a 133mm x 120mm (5.2" x 4.7") rectangular hole in the surface of the furniture. Maximum table thickness is 7.6cm (3")

Note - The power socket module is not included. Purchase the country-specific module separately



KRAMER

TECHNICAL SPECIFICATIONS

PORTS:	1 HDMI connector, 1 Ethernet RJ-45 connector, 1 15-pin HD connector, 1 3.5mm mini jack
POWER SOCKET ASSEMBLIES:	USA Universal 100–240V AC, 50/60Hz, 5A per outlet; 100–220V AC, 50/60Hz, 5A per outlet; Germany and EU 100–240V AC, 50/60Hz, 5A per outlet; Belgium and France 100–240V AC, 50/60Hz, 5A per outlet; Italy 100–240V AC, 50/60Hz, 5A per outlet; Australia 100–240V AC, 50/60Hz, 5A per outlet; Israel 220V AC, 50/60Hz, 5A per outlet; South Africa 220V AC, 50/60Hz, 5A per outlet; Switzerland 220V AC, 50/60Hz, 5A per outlet; UK 220V AC, 50/60Hz, 5A per outlet; Brazil 220V AC, 50/60Hz, 5A per outlet
OPERATING TEMPERATURE RANGE:	+5° to +45°C (41° to 113°F)
OPERATING HUMIDITY RANGE:	10 to 90% RHL, non-condensing
STORAGE TEMPERATURE RANGE:	-20° to +70°C (-4° to 158°F)
STORAGE HUMIDITY RANGE:	5 to 95% RHL, non-condensing
INCLUDED ACCESSORIES:	Cardboard template
OPTIONS:	Power socket kits, power cord



KRAMER

CONFIGURATIONS

TBUS-201XL(B) Enclosure - Black Sand Blasted Anodized Aluminum Top

TBUS-201XL(BC) Enclosure - Silver Sand Blasted Anodized Aluminum Top

