



VM-24HC

2x1:4 Compact HDMI Switchable DA

| HDMI | HDCP Compliant



The VM24HC is a highperformance switcher and distribution amplifier for HDMI signals. The unit accepts one of two HDMI inputs and distributes the selected signal to four HDMI outputs

FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphics channel)

HDTV Compatible

HDCP Compliant

EDID Pass-through - Pass-through algorithm ensures Plug and Play operation for HDMI source and display systems

EDID Handling - Acquires the EDID from one output, from all connected outputs (automix) or uses a default EDID

Kramer Equalization & re-Klocking™ Technology - Rebuilds the digital signal to travel longer distances

HDMI Support - With Deep Color, x.v.Color™, up to 7.1 Uncompressed Audio Channels

3D Pass-Through

Flexible Control Options - Front panel, IR remote & RS232

Desktop Size - Compact size. 2 units can be rack mounted sidebyside in a 1U rack space with the recommended rack adapter



KRAMER

TECHNICAL SPECIFICATIONS

INPUTS:	2 HDMI connectors
OUTPUTS:	4 HDMI connectors
MAX. DATA RATE:	6.75Gbps (2.25Gbps per graphic channel)
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI and HDCP
CONTROLS:	EDID SELECT, EDID READ, IN 1, IN 2 buttons, RS232, IR
INDICATORS:	POWER, IR, OUTPUT LEDs
POWER CONSUMPTION:	5V DC, 1.1A
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	40° to +70°C (40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
Accessories	Included Power supply
Product Dimensions	21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H
Product Weight	0.9kg (1.9lbs) approx
Shipping Dimensions	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H
Shipping Weight	1.4kg (3.0lbs) approx

