



## VS-84H2

8x4 4K HDR HDCP 2.2 Matrix Switcher with Digital Audio Routing

| HDMI | Ethernet - RJ-45 | 4K/60 UHD (4:4:4)



VS84H2 is a highperformance 8x4 matrix switcher for 4K@60Hz (4:4:4) HDR signals and digital audio routing. It reclocks and equalizes the signals and can route any one of 8 HDMI, HDCPcompliant sources (selectable) to any or all outputs simultaneously. VS84H2 offers unmatched audio flexibility where any embedded digital audio input can be routed to any digital output in addition to four ARC sources to produce an equivalent 12x8 audio matrix

## FEATURES

**High-Performance AV Matrix** - Switches 8 4K@60Hz (4:4:4), HDR, HDMI, HDCP (2.2/1.4)compliant signals to 4 4K@60Hz (4:4:4), HDR, HDMI, HDCP (2.2/1.4)compliant outputs at up to 18G data rate. Featuring Kramer reClocking™ and Equalization Technology that rebuilds the digital signal to travel longer distances. Note: For optimum range and performance, use recommended Kramer cables

**HDMI Support** - Deep Color, 3D, ARC, up to 7.1 uncompressed audio channels as specified in HDMI 2.0

**Independent Audio Routing** - Any embedded digital audio input can be routed to any digital output, in addition to ARC sources, to produce an equivalent 12x8 audio matrix (8 embedded digital inputs + 4 ARC inputs and 4 digital outputs + 4 ARC outputs)

**Easy Step-In Collaboration Function** - When used with a Kramer Step-In enabled switcher, just plug in your device and press the Step-In button. Your device becomes the active signal on the main display

**EDID Management** - Individual EDID management per input. Captures and stores the EDID from a display device

**Flexible Content Protection** - Selectable HDCP per input

**Quick Access to Common Configurations** - Save up to 16 preset configurations

**Smart Switching** - Active source & acceptor detection. Automatic input selection based on priority selection or last connected input

**Embedded Pattern Generator** - With selectable patterns

**Convenient Unit Control and Configuration Options** - Local control via front panel switching, memory, lock and EDID buttons, and Input/Output LED display. Distance control via userfriendly embedded web pages via the Ethernet, Protocol 3000 API, and RS232 serial commands transmitted by a PC, touch screen system or other serial controller

**Cost-Effective Maintenance** - Input selection indicators facilitate easy local maintenance and troubleshooting. Firmware upgrade via Ethernet or mini USB

**Easy Installation** - 19" enclosure for rack mounting in a 1U rack space with included rack ears and universal 100240V AC power supply



# KRAMER

## TECHNICAL SPECIFICATIONS

Inputs	8 HDMI: On female HDMI connectors
Outputs	4 HDMI: On female HDMI connectors
Ports	1 Ethernet: On an RJ-45 connector 1 RS-232: On a 3-pin terminal block connector 1 USB: On a USB type A connector, for powering an external device 1 USB: On a mini USB connector, for firmware upgrade or communication with a PC or serial controller
Video	HDMI Support: Deep Color, 3D, ARC, up to 7.1 uncompressed audio channels as specified in HDMI 2.0 Content Protection: HDCP 2.2 Max. Output Resolution: 4K@60Hz (4:4:4)
User Interface	Control: Input/output selection, mute, test pattern, memory, front panel lock, buttons. RS-232 serial commands transmitted by a PC, touch screen system or other serial controller, embedded web pages via LAN for configuration and control Indicators: Input/output LCD display
Power	Source: 100–240V AC 50/60Hz Consumption: 600mA
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: –40° to +70°C (–40° to 158°F) Humidity: 10% to 90%, RH (non-condensing)
Accessories	Included: Rack ears, rubber feet, power cord
Product Dimensions	43.64cm x 18.30cm x 4.36cm (17.18" x 7.20" x 1.72" ) W, D, H
Product Weight	2.1kg (4.6lbs) approx
Shipping Dimensions	52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21" ) W, D, H
Shipping Weight	2.9kg (6.4lbs) approx

