

VS-211H2

2x1 4K HDR HDCP 2.2 HDMI Auto Switcher

| HDMI | HDCP Compliant | 4K/60 UHD (4:2:0) | 4K/60 UHD (4:4:4) | HDCP 2.2 Compatible



VS-211H2 is a high-performance automatic switcher for 4K HDR, HDCP 2.2, HDMI 2.0 video signals. Offering priority and last-connected switching options, it automatically switches according to the selected switching scheme based on active video signal detection

FEATURES

Max. Data Rate - 17.82Gbps (5.94Gbps per data channel)

Max. Resolution - 4K@60Hz (4:4:4)

Kramer Equalization and re-Klocking Technology

HDR Support

HDTV Compatible

HDMI 2.0 & HDCP 2.2 Compliant

3D Pass-Though



TECHNICAL SPECIFICATIONS

INPUTS: 2 HDMI connectors

OUTPUTS: 1 HDMI connector

Max. Data Rate 17.82GBPS (5.94Gbps per graphic channel)

Max. Resolution 4K@60Hz (4:4:4)

Standards Compliance HDR10, HDCP 2.2 (does not support conversion to HDCP 1.4), HDMI 2.0

CONTROLS: Status/priority DIP-switches, contact closure remote control

REGULATORY EMC EN 55032;IEC 60950-1(ed.2);IEC 60950-1(ed.2)am1;IEC 60950-1(ed.2)am2

CERTIFICATION:

OPERATING 0° to +40°C (32° to 104°F)

TEMPERATURE:

 -40° to $+70^{\circ}$ C (-40° to 158° F)

STORAGE TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing

POWER

CONSUMPTION:

5V DC, 400mA

INCLUDED ACCESSORIES: Power supply 5.2V DC/4A desktop

PRODUCT

DIMENSION:

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

PRODUCT WEIGHT: 0.2kg (0.4lbs) approx

SHIPPING

15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

DIMENSION:

SHIPPING WEIGHT: 0.6kg (1.4lbs) approx

