Technical Information

Product Description Substance weight Caliper	GLOSS CLEAR INKJET 40# WHITE KRAFT GLOSS CLEAR INKJET 40# WHITE KRAFT 124 lbs./ream (25"x38") 5.9 mil
Face	POLYJET CLEAR PET
Product Use Substance weight Caliper	Glossy, clear PET film, specifically top coated to receive dye and pigment-based ink-jet inks. Capable of printing photo-realistic images that are resistant to water and other semi-harsh chemicals. Ibs/ream 67 (25in x TAPPI-410 38in) 3.10 mil TAPPI-411
Additional info Shelf life	Facestock contact with noxious fumes from chemicals, lift trucks, etc. should be avoided. 1 year.
Adhesive	·
	RP37
Type Composition Use	Clear permanent adhesive. Emulsion acrylic. Designed specifically for applications requiring excellent wet-out properties, clarity, and UV-stability. Good adhesion properties and heat resistance.
Tack	9 N FTM 9
Shear	10 h FTM 8
PE-Looptack	5.0 N modified FTM 9
Minimum labelling temperature Service temperature minimum Service temperature maximum Shelf life Limitations	23 °F -20 °F 212 °F From the date of manufacture: 2 years at 68°F and RH 50%. Limited adhesion at low temperatures. The highest end-use temperature must be separately checked together with the face material.
Liner	40# WHITE KRAFT
Product Use Substance weight	White kraft liner. For roll-to-roll applications and photocell dispensing. lbs/ream 42 (24in x TAPPI-410 36in)
Caliper	2.40 mil TAPPI-411
Tensile strength MD	40 lbf/in TAPPI-494
Tensile strength CD Opacity	18 lbf/in TAPPI-494 61 % TAPPI-425
Disclaimer	The above are typical technical values and are given in good faith based upon our most up to date knowledge and experience. As the products are used outside of our control we cannot take

products are used outside of our control we cannot take responsibility for any damage which may be caused using the

product.