






Antarktíós - RGB Light

Carlotta de Bevilacqua



IP65   



LUMINAIRE

- Watt: **3W**
- Delivered lumens output: **20lm**
- CRI: **80**

Notes

Driver supplied separately.

DESCRIPTION

An innovative patented optic realizes a light blade that, from a single LED source, draws a 360 ° light profile. A perfect tool for architectural lighting that emphasizes with high efficiency the different opening profiles

PRODUCT CODE: T4521030

FEATURES

- Article Code: **T4521030**
- Colour: **Aluminium**
- Installation: **CeilingWallFloor**
- Series: **Architectural Outdoor**
- Environment: **Outdoor**
- design by: **Carlotta de Bevilacqua**

DIMENSIONS

- Length: **cm 11.7**
- Width: **cm 5.2**
- Height: **cm 8.1**
- Impact Resistance: **IK06**

Accessories

NO
IMAGE
AVAILABLE

Driver 25W - 100-277 Vac - 12Vdc - 148x40x32
(LxWxH) - IP67 DV1055

NO
IMAGE
AVAILABLE

Driver 40W - 100-277 Vac - 12Vdc - 163x43x32
(LxWxH) - IP67 DV1056

NO
IMAGE
AVAILABLE

Driver 100W - 100-277 Vac - 12Vdc - 140x63x32
(LxWxH) - IP67 DV1057

NO
IMAGE
AVAILABLE

Driver 150W - 100-277 Vac - 12Vdc - 228x68x39
(LxWxH) - IP67 DV1043

NO
IMAGE
AVAILABLE

Dimmer DMX - 12-24 Vdc 12-24 pwm - 88x54x25
(LxWxH) - IP20 DV1059

NO
IMAGE
AVAILABLE

Dimmer DALI - 12-24 Vdc 12-24 pwm - 88x54x25
(LxWxH) - IP20 DV1052