



## 022-6053 through 022-6056

### Evacuation/Descent System

#### FEATURES :

- Lightweight aluminum bidirectional descent device with swivel carabiner
- Assisted or unassisted descent capabilities
- Dual brake pad heat-dissipating housing with 1:8:2 gear ratio
- 2 Integral rope belays
- Built-in rope lock
- Rated for use by 1 or 2 persons
- Low stretch ANSI compliant kernmantle rope with captive eye and steel carabiner
- FS810-3 - 3' reinforced cross arm strap anchor
- 018-9001 - 36" rope protector
- 023-9087 - Rescue Gear Bag
- Max descent length: 525' (160m)
- Anchor strength requirement: 3,100 lbs. (1400 kg)

#### ITEM WEIGHT :

- Weight varies per length



USER WEIGHT CAPACITY	
ANSI	1 person: 110-310 lbs. (50-141 kg)
OSHA	2 person: Up to 620 lbs. (281 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.4-2013
OSHA	1910.140, 1926.502

SIZE(S)		
022-6053	200 Feet (61 m)	21.1 lbs. (9.6 kg)
022-6054	300 Feet (91 m)	25.1 lbs. (11.4 kg)
022-6055	400 Feet (122 m)	29.1 lbs. (13.2 kg)
022-6056	500 Feet (152 m)	33.1 lbs. (15.0 kg)

MATERIAL SPECIFICATION	
Descent device	Aluminum, stainless steel, nylon
Rope	9.3 mm nylon/polyester kernmantle
Rope protector	Water repellent tarpaulin
Cross arm strap	Polyester, zinc plated alloy steel
Bag	Water repellent tarpaulin
Swivel carabiner	Zinc plated steel
Rope carabiner	Yellow chromate plated steel