



Fall Protection

3M™ DBI-SALA® Sliding Beam Anchor

Smooth operator.

Mobility. It's critical to getting the job done, just like your fall protection. With the new 3M™ DBI-SALA® Sliding Beam Anchor, you can get the best of both worlds. Once you secure it to the beam using the redesigned adjustment buttons, simply connect your Self-Retracting Lifeline (SRL)* or lanyard to the swiveling D-ring and you're ready to work. The anchor point slides effortlessly behind you.



* Use 3M™ DBI-SALA® Nano-Lok™ edge Twin-Leg Quick-Connect Self-Retracting Lifeline – Cable when tying off at feet.

3M™ DBI-SALA® Sliding Beam Anchor

Applications:

- ▶ Bridge work
- ▶ Buildings
- ▶ Warehouses
- ▶ Arenas
- ▶ Parking ramps

Completely redesigned:

- ▶ Versatile size ranges to fit a variety of beams
- ▶ Replaceable wear pads
- ▶ 360-degree swiveling D-ring anchor point
- ▶ Integrated dual ratcheting system
- ▶ High-strength, lightweight steel and aluminum construction
- ▶ 5,000 lb. (22 kN) strength and up to 420 lb. (189 kg) capacity

Model shown
2104715

Model shown
2104710

Hands-free mobility
360-degree swiveling D-ring optimizes your mobility on the beam.

Rugged durability
Corrosion-resistant construction meets ANSI standards for weather, environmental and storage conditions.

Visible adjustability
Dual ratcheting adjustment buttons are accessible above the beam, while locking mechanism is located on the side to reduce accidental engagement.


Lightweight
Compact size and lightweight materials.

Easy pad replacement
Snap-in design of wear pads allows them to be replaced quickly in the field.

Compliant
Meets ANSI Z359.18 Anchorage Connector standard; OSHA 420 lb./ANSI 310 lb. ratings.

Ordering Information

| Part # | Beam Width | Flange Thickness | Description |
|---------|------------|------------------|---|
| 2104710 | 3.5-14 in. | 1.25 in. | Sliding Beam Anchor, Small (ANSI/OSHA) |
| 2104715 | 12-30 in. | 2.5 in. | Sliding Beam Anchor, Large (ANSI/OSHA) |
| 2110815 | - | - | Replacement wear pads (Small, Set of 2) |
| 2110816 | - | - | Replacement wear pads (Large, Set of 2) |



For foot level tie-off, use 3M™ DBI-SALA® Nano-Lok™ edge Twin-Leg Quick-Connect Self-Retracting Lifeline – Cable, 8 ft. (2.4 m)

Model shown
3500225

Find these products and more at [3M.com/FallProtection](https://www.3m.com/FallProtection).



3M Fall Protection
3833 SALA Way
Red Wing, MN 55066 USA

Phone 800.328.6146
Email 3mfallprotection@mmm.com
Web [3M.com/FallProtection](https://www.3m.com/FallProtection)

3M, DBI-SALA and Nano-Lok are trademarks of 3M Company and its affiliates. © 3M 2018. All rights reserved.