

721530LE

FT-R™ Class 2 Leading Edge SRL with 30' Galvanized Steel Cable

Features :

- 20% lighter than typical 30' Cable Class 2 Leading Edge SRLs
- 7/32" galvanized steel cable lifeline with swivel snap hook
- Innovative energy absorber design provides more consistent performance in all environmental conditions and features full fall clearance diagrams and charts inside the Viewpack®
- Improved internal mechanism design minimizes unintentional lockups to keep workers moving freely and productively
- Swiveling anchor and leg-end connectors plus an integrated carrying handle simplify installation and transportation
- Industry first UV-resistant and scratch resistant label keep warnings legible and units in service
- Includes steel anchorage carabiner with 3/4" gate opening
- Complies with ANSI Z359.14-2021 Class 2 SRL. [Learn more and download White Paper](#)

Material Specifications		Performance Specifications		Compliant With:	
Cable	7/32" galvanized steel; 3,600 lb min. static strength	Static Strength	3,600 lb min.	OSHA	1926.502 and 1910.66
Energy Absorber	Polyester tear-away	ANSI SRL Class/Type	Class 2 SRL	CSA	Z259.2.2-2017
Lifeline Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength	Avg. Arrest Force	1,350 lb max.	ANSI	Z359.14-2021
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength	Max. Arrest Force	1,800 lb		
		Max. Arrest Distance	42"		
		ANSI User Capacity	130 to 310 lb max.		
		OSHA User Capacity	130 to 310 lb max.		

Sizes & Part Numbers			
721520LE - 20'	721530LE - 30'	721560LE - 60'	