

## 7227CLE

DuraTech® Leading Edge Class 2 SRL with 20' Galvanized Steel Cable and Aluminum Housing

### Features :

- 7/32" galvanized steel cable lifeline with load-indicating swivel snap hook
- Internal inertial braking system with dual disc brakes provides superior deceleration.
- Integrated external ViewPack® energy absorber enhances braking system and preserves lifeline integrity
- Side-payout housing design and lifeline recoil spring deliver smooth operation and help reduce nuisance lock-up
- Integrated lifeline hand-grip simplifies dorsal connection
- Stackable aluminum housing design and handle provide easy installation and storage
- Includes extra large anchorage carabiner with 2-1/4" gate opening
- Complies with ANSI Z359.14-2021 Class 2 SRL. [Learn more and download White Paper](#)

Material Specifications		Performance Specifications		Compliant With:	
<b>Cable</b>	7/32" galvanized steel; 3,600 lb min. static strength	<b>Static Strength</b>	3,600 lb min.	<b>ANSI</b>	Z359.14-2021
<b>Energy Absorber</b>	Polyester tear-away	<b>ANSI SRL Class/Type</b>	Class 2 SRL	<b>OSHA</b>	1926.502 and 1910.66
<b>Lifeline Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength	<b>Avg. Arrest Force</b>	1,350 lb		
<b>Anchorage Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength	<b>Max. Arrest Force</b>	1,800 lb		
		<b>Max. Arrest Distance</b>	42"		
		<b>ANSI User Capacity</b>	130 to 310 lb max.		
		<b>OSHA User Capacity</b>	130 to 310 lb max.		

Sizes & Part Numbers					
7226CLE - 15'	7227CLE - 20'	7232CLE - 30'	7268CLE - 50'	7265CLE - 60'	