

7232CLE

DuraTech® Leading Edge Class 2 SRL with 30' Galvanized Steel Cable and Aluminum Housing

Features :

- 7/32" galvanized steel cable lifeline with load-indicating swivel snap hook
- Internal inertial braking system with dual disc brakes provides superior deceleration.
- Integrated external ViewPack® energy absorber enhances braking system and preserves lifeline integrity
- Side-payout housing design and lifeline recoil spring deliver smooth operation and help reduce nuisance lock-up
- Integrated lifeline hand-grip simplifies dorsal connection
- Stackable aluminum housing design and handle provide easy installation and storage
- Includes extra large anchorage carabiner with 2-1/4" gate opening
- Complies with ANSI Z359.14-2021 Class 2 SRL. [Learn more and download White Paper](#)

Material Specifications	
Cable	7/32" galvanized steel; 3,600 lb min. static strength
Energy Absorber	Polyester tear-away
Lifeline Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI SRL Class/Type	Class 2 SRL
Avg. Arrest Force	1,350 lb
Max. Arrest Force	1,800 lb
Max. Arrest Distance	42"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
ANSI	Z359.14-2021
OSHA	1926.502 and 1910.66

Sizes & Part Numbers					
7226CLE - 15'	7227CLE - 20'	7232CLE - 30'	7268CLE - 50'	7265CLE - 60'	