

## 727630C

### Contractor C Class 1 SRL with 30' Galvanized Cable and Anchorage Carabiner

#### Features :

- 3/16" galvanized steel cable lifeline with load-indicating swivel snap hook
- Features glass-filled nylon housing for durable impact resistance.
- Lifeline includes recoil spring bumper to reduce retraction lock-up
- Rugged internal steel drum and inertial braking system deliver reliable performance
- SRL includes double-locking twist-lock anchorage carabiner
- Complies with ANSI Z359.14-2021 Class 1 SRL. [Learn more and download White Paper](#)

Material Specifications		Performance Specifications		Compliant With:	
<b>Cable</b>	3/16" galvanized steel; 3,600 lb min. static strength	<b>Static Strength</b>	3,600 lb min.	<b>ANSI</b>	Z359.14-2021
<b>Lifeline Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength	<b>ANSI SRL Class/Type</b>	Class 1 SRL	<b>OSHA</b>	1926.502 and 1910.66
<b>Anchorage Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength	<b>Avg. Arrest Force</b>	900 lb		
		<b>Max. Arrest Force</b>	1,800 lb		
		<b>Max. Arrest Distance</b>	42"		
		<b>ANSI User Capacity</b>	130 to 310 lb max.		
		<b>OSHA User Capacity</b>	130 to 310 lb max.		

Sizes & Part Numbers					
727620 -20' (ANSI Compliant)	727630C - 30' (ANSI Compliant)	C727630 - 30' (CSA Compliant)	727650C - 50' (ANSI Compliant)	C727650 - 50' (CSA Compliant)	7276100 - 100' (ANSI Compliant)