

## 727630LE

### Contractor Leading Edge Class 2 SRL with 30' Galvanized Steel Cable and Anchorage Carabiner

#### Features :

- 7/32" galvanized steel cable lifeline with load-indicating swivel snap hook
- Internal inertial braking system provides positive stopping action and uniform deceleration.
- Integrated external ViewPack® energy absorber strengthens the braking system and preserves lifeline integrity
- Durable glass-filled nylon housing extends service life
- Integrated lifeline hand-grip simplifies dorsal connection and recoil spring helps prevent lifeline lock-up
- Load-indicating snap hook provides visual fall event indication
- Complies with ANSI Z359.14-2021 Class 2 SRL. [Learn more and download White Paper](#)

Material Specifications	
<b>Cable</b>	7/32" galvanized steel; 3,600 lb min. static strength
<b>Energy Absorber</b>	Polyester tear-away
<b>Lifeline Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Anchorage Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
<b>Static Strength</b>	3,600 lb min.
<b>ANSI SRL Class/Type</b>	Class 2 SRL
<b>Avg. Arrest Force</b>	1,350 lb
<b>Max. Arrest Force</b>	1,800 lb
<b>Max. Arrest Distance</b>	42"
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 310 lb max.

Compliant With:	
<b>ANSI</b>	Z359.14-2021
<b>OSHA</b>	1926.502 and 1910.66
<b>CSA</b>	Z259.2.2-2017

Sizes & Part Numbers				
727620LE - 20' (ANSI Compliant)	727630LE - 30' (ANSI Compliant)	C727630LE - 30' (CSA Compliant)	727650LE - 50' (ANSI Compliant)	C727650LE - 50' (CSA Compliant)