

## 7276BWR

### 20' Contractor Web Class 1 SRL with Swivel Aluminum Carabiner

#### Features :

- Dyneema® web lifeline resists abrasion while providing trusted strength
- Glass-filled nylon housing over internal steel frame provides unmatched impact resistance.
- Internal braking system and external energy absorber combine for positive stopping and smooth deceleration
- External energy absorber features ViewPack® cover with inspection window and WrapPack label protection
- Features aluminum alloy swivel carabiner lifeline connector
- Includes alloy steel anchorage carabiner
- Complies with ANSI Z359.14-2021 Class 1 SRL. [Learn more and download White Paper](#)

Material Specifications		Performance Specifications		Compliant With:	
<b>Webbing</b>	Dyneema®; 4,500 lb min.	<b>Static Strength</b>	3,600 lb min.	<b>OSHA</b>	1926.502 and 1910.66
<b>Energy Absorber</b>	Polyester tear-away	<b>ANSI SRL Class/Type</b>	Class 1 SRL	<b>ANSI</b>	Z359.14-2021
<b>Lifeline Connector</b>	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength	<b>Avg. Arrest Force</b>	900 lb		
<b>Anchorage Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength	<b>Max. Arrest Force</b>	1,800 lb		
		<b>Max. Arrest Distance</b>	42"		
		<b>ANSI User Capacity</b>	130 to 310 lb max.		
		<b>OSHA User Capacity</b>	130 to 310 lb max.		

#### Sizes & Part Numbers

7276BWR (ANSI)	C7276BWR (CSA)	
----------------	----------------	--