

72906SC5

6' Arc Flash DuraTech® Mini Class 1 Personal SRL-P with Aluminum Rebar Hook, Includes Steel Dorsal Connecting Carabiner

Features :

- Kevlar® web lifeline protects against Arc Flash hazards
- Energy absorber features Nomex® ViewPack® cover with inspection window and WrapPack label protection.
- Features internal locking pawls and external energy absorber for even deceleration
- Nylon housing provides impact resistance in most worksite conditions
- Plated steel swivel-eye helps to prevent lifeline twisting and provide smooth operation
- Features aluminum alloy rebar hook anchorage connector
- Rebar hook features transverse load rated gate
- Includes alloy steel dorsal connecting carabiner
- May be anchored up to 5' below the dorsal D-ring for user's weighing up to 310 lb max.
- Complies with ANSI Z359.14-20121 Class 1 SRL-P and ASTM F887-13. [Learn more and download White Paper](#)

Material Specifications	
Webbing	Kevlar®; 4,500 lb min.
Energy Absorber	Polyester tear-away
Anchorage Connector	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength
Dorsal Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI SRL Class/Type	Class 1 SRL-
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
Max. Arrest Distance	42"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
OSHA	1926.502 and 1910.66
ANSI	Z359.14-2021
ASTM	F887-13