

72906SC6L

6' Arc Flash DuraTech® Mini Class 1 Personal SRL-P with Aluminum Dorsal Connecting Carabiner and Steel Anchorage Carabiner

Features :

- Kevlar® web lifeline protects against Arc Flash hazards
- Energy absorber features Nomex® ViewPack® cover with inspection window and WrapPack label protection.
- Features internal locking pawls and external energy absorber for even deceleration
- Nylon housing provides impact resistance in most worksite conditions
- Plated steel swivel-eye helps to prevent lifeline twisting and provide smooth operation
- Features alloy steel carabiner anchorage connector with Kevlar® extension for lift connections
- Includes aluminum alloy dorsal connecting carabiner
- May be anchored up to 3' below the dorsal D-ring for user's weighing up to 310 lb max
- Complies with ANSI Z359.14-20121 Class 1 SRL-P and ASTM F887-20. [Learn more and download White Paper](#)

Material Specifications	
Webbing	Kevlar®; 4,500 lb min.
Energy Absorber	Polyester tear-away
Anchorage Connector	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength
Dorsal Connector	Plated alloy steel; 5,000 lb min. static strength with 5,000 lb gate strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI SRL Class/Type	Class 1 SRL-
Avg. Arrest Force	900 lb
Max. Arrest Force	1,800 lb
Max. Arrest Distance	42"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
OSHA	1926.502 and 1910.66
ASTM	F887-20
ANSI	Z359.14-2021