

72907SP8S

7' Arc Flash Mini Pro™ Class 1 Personal SRL-P, Single-leg with Steel 5k Snap Hook

Features :

- Kevlar® web lifeline protects against Arc Flash hazards
- Features comprehensive fall clearance charts and tables inside the Kevlar®/Nomex® energy absorber cover
- Compact design elevates the SRDs to align optimally with worker motion, increasing both comfort and productivity
- Features alloy steel carabiner with 5,000 lbs. rated gate for tie-back connections
- Suitable for below D-ring tie-off up to five feet when no edge hazards exist; outside the scope of ANSI Z359
- Rated for workers weighing up to 420 pounds, including clothes, tools, gear, etc.
- Complies with ANSI Z359.14-20121 Class 1 SRL-P and ASTM F887-20. [Learn more and download White Paper](#)
- Meets ASTM F887 Standards



Material Specifications	
Webbing	Kevlar®; 4,500 lb min.
Energy Absorber	Polyester tear-away
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 5,000 lb gate strength
Dorsal Connector	Aluminum alloy; 3,600 lb min.

Performance Specifications	
Static Strength	3,600 lb min.
ANSI SRL Class/Type	Class 1 SRL-
Avg. Arrest Force	1,350 lb max.
Max. Arrest Force	1,800 lb
Max. Arrest Distance	42"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 420 lb max.

Compliant With:	
ASTM	F887-20
ANSI	Z359.14-2021
OSHA	1926.502 and 1910.66