

82808TPOS

8' FT-X™ Cable Class 2 Leading Edge Personal SRL-P, Twin-leg with Steel Swivel Mini Rebar Hook

Features :

- Lightest SRL in its class with less than 5 lbs. of effective weight on the back while device is in use
- Compact design elevates the SRDs to align optimally with worker motion, increasing both comfort and productivity
- Features comprehensive fall clearance charts and tables inside the energy absorber cover
- Internal mechanism design minimizes unintentional lockups to keep you moving freely and productively
- Suitable for below D-ring tie-off up to five feet and leading edge exposures and hazards, including steel and precast concrete
- Rated for workers weighing up to 420 pounds, including clothes, tools, gear, etc.
- Features SpeedLink™ field replaceability of damaged retractable units, lowering overall cost of ownership and reducing equipment down time. [Request SpeedLink™ Spanner Tool](#)
- Replacement retractable part number is 82808RP0S
- Complies with ANSI Z359.14-2021 Class 2 SRL-P. [Learn more and download White Paper](#)

| Material Specifications | |
|----------------------------|---|
| Cable | 3/16" galvanized steel; 3,600 lb min. static strength |
| Energy Absorber | Polyester tear-away |
| Anchorage Connector | Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength |
| Dorsal Connector | Aluminum alloy; 3,600 lb min. |

| Performance Specifications | |
|-----------------------------|--------------------|
| Static Strength | 3,600 lb min. |
| ANSI SRL Class/Type | Class 2 SRL- |
| Avg. Arrest Force | 1,350 lb max. |
| Max. Arrest Force | 1,800 lb |
| Max. Arrest Distance | 42" |
| ANSI User Capacity | 130 to 310 lb max. |
| OSHA User Capacity | 130 to 420 lb max. |

| Compliant With: | |
|-----------------|----------------------|
| OSHA | 1926.502 and 1910.66 |
| ANSI | Z359.14-2021 |
| CSA | Z259.2.2-2017 |