

## 84008SPO

### 8' FT-X™ EdgeCore™ Arc Flash Class 2 Leading Edge Personal SRL-P, Single-leg with Steel Mini Rebar Hook

#### Features :

- Arc Flash rating AND Class 2 Leading Edge rating for the first time in an SRL.
- Features 100% Kevlar® version of FallTech's innovative EdgeCore™ synthetic lifeline
- Compact design elevates the SRDs to align optimally with worker motion, increasing both comfort and productivity
- Features comprehensive fall clearance charts and tables inside the Kevlar®/Nomex® energy absorber cover
- Internal mechanism design minimizes unintentional lockups to keep you moving freely and productively
- Suitable for below D-ring tie-off up to five feet and leading edge exposures and hazards, including steel and precast concrete
- Rated for workers weighing up to 420 pounds, including clothes, tools, gear, etc.
- Complies with ANSI Z359.14-2021 Class 2 SRL-P. [Learn more and download White Paper](#)
- Meets ASTM F887 Standards

Material Specifications	
<b>Lifeline</b>	EdgeCore™ Arc Flash (Kevlar®); 5,000 lb min. static strength
<b>Energy Absorber</b>	Polyester tear-away
<b>Anchorage Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Dorsal Connector</b>	Aluminum alloy; 3,600 lb min.

Performance Specifications	
<b>Static Strength</b>	3,600 lb min.
<b>ANSI SRL Class</b>	Class 2 SRL-
<b>Avg. Arrest Force</b>	1,350 lb max.
<b>Max. Arrest Force</b>	1,800 lb
<b>Max. Arrest Distance</b>	42"
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 420 lb max.

Compliant With:	
<b>ASTM</b>	F887-20
<b>OSHA</b>	1926.502 and 1910.66
<b>ANSI</b>	Z359.14-2021