PRODUCT SPECIFICATIONS



84008SP3S

8' FT-X™ EdgeCore™ Arc Flash Class 2 Leading Edge Personal SRL-P, Single-leg with Steel Swivel Rebar Hook

Features:

- Arc Flash rating AND Class 2 Leading Edge rating for the first time in an SRL.
- Features 100% Kevlar® version of FallTech's innovative EdgeCore™ synthetic lifeline
- Compact design elevates the SRDs to align optimally with worker motion, increasing both comfort and productivity
- Features comprehensive fall clearance charts and tables inside the Kevlar®/Nomex® energy absorber cover
- Internal mechanism design minimizes unintentional lockups to keep you moving freely and productively
- Suitable for below D-ring tie-off up to five feet and leading edge exposures and hazards, including steel and precast concrete
- Rated for workers weighing up to 420 pounds, including clothes, tools, gear, etc.
- Complies with ANSI Z359.14-2021 Class 2 SRL-P. <u>Learn more and download White</u> <u>Paper</u>
- Meets ASTM F887 Standards

Material Specifications	
Lifeline	EdgeCore™ Arc Flash (Kevlar®); 5,000 lb min. static strength
Energy Absorber	Polyester tear-away
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Dorsal Connector	Aluminum alloy; 3,600 lb min.

Performance Specifications		
Static Strength	3,600 lb min.	
ANSI SRL Class	Class 2 SRL-	
Avg. Arrest Force	1,350 lb max.	
Max. Arrest Force	1,800 lb	
Max. Arrest Distance	42"	
ANSI User Capacity	130 to 310 l max.	
OSHA User Capacity	130 to 420 lb max.	

Compliant With:		
ASTM	F887-20	
OSHA	1926.502 and 1910.66	
ANSI	Z359.14-2021	