

84008TP3S

8' FT-X™ EdgeCore™ Arc Flash Class 2 Leading Edge Personal SRL-P, Twin-leg with Steel Swivel Rebar Hooks

Features :

- Arc Flash rating AND Class 2 Leading Edge rating for the first time in an SRL.
- Features 100% Kevlar® version of FallTech's innovative EdgeCore™ synthetic lifeline
- Compact design elevates the SRDs to align optimally with worker motion, increasing both comfort and productivity
- Features comprehensive fall clearance charts and tables inside the Kevlar®/Nomex® energy absorber cover
- Internal mechanism design minimizes unintentional lockups to keep you moving freely and productively
- Suitable for below D-ring tie-off up to five feet and leading edge exposures and hazards, including steel and precast concrete
- Rated for workers weighing up to 420 pounds, including clothes, tools, gear, etc.
- Features SpeedLink™ field replaceability of damaged retractable units, lowering overall cost of ownership and reducing equipment down time. [Request SpeedLink™ Spanner Tool](#)
- Replacement retractable part number is 84008RP3S
- Complies with ANSI Z359.14-2021 Class 2 SRL-P. [Learn more and download White Paper](#)
- Meets ASTM F887 Standards

Material Specifications	
Lifeline	EdgeCore™ Arc Flash (Kevlar®); 5,000 lb min. static strength
Energy Absorber	Polyester tear-away
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Dorsal Connector	Aluminum alloy; 3,600 lb min.

Performance Specifications	
Static Strength	3,600 lb min.
ANSI SRL Class	Class 2 SRL-
Avg. Arrest Force	1,350 lb max.
Max. Arrest Force	1,800 lb
Max. Arrest Distance	42"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 420 lb max.

Compliant With:	
ASTM	F887-20
OSHA	1926.502 and 1910.66
ANSI	Z359.14-2021