

## 84711SC3

11' FT-X™ Web Class 1 SRL-P with Steel Rebar Hook, Includes Steel Dorsal Connecting Carabiner

### Features :

- Dyneema® web lifeline provides ultimate durability with industry proven strength
- ViewPack® external energy absorber includes comprehensive fall clearance charts inside the cover
- Internal mechanism design minimizes unintentional lockups to keep you moving freely and productively
- Engineering housing material provides durability at low weight. Light green color denotes the non-leading edge capability of Class 1 SRLs
- Features plated alloy steel rebar hook leg-end connector
- Includes plated alloy steel connecting carabiner
- Rated for workers weighing up to 420 pounds, including clothes, tools, gear, etc.
- May be anchored up to 5' below the dorsal D-ring with no edge hazards for user's weighing up to 310 lb max.
- Complies with ANSI Z359.14-2021 Class 1 SRL-P. [Learn more and download White Paper](#)

| Material Specifications     |   |
|-----------------------------|---|
| <b>Webbing</b>              | Dyneema®; 4,500 lb min.   |
| <b>Energy Absorber</b>      | Polyester tear-away   |
| <b>Leg-End Connector</b>    | Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength |
| <b>Swivel Eye Connector</b> | Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength |

| Performance Specifications  |                    |
|-----------------------------|--------------------|
| <b>Static Strength</b>      | 3,600 lb min.      |
| <b>ANSI SRL Class/Type</b>  | Class 1 SRL-       |
| <b>Avg. Arrest Force</b>    | 1,350 lb max.      |
| <b>Max. Arrest Force</b>    | 1,800 lb           |
| <b>Max. Arrest Distance</b> | 42"                |
| <b>ANSI User Capacity</b>   | 130 to 310 lb max. |
| <b>OSHA User Capacity</b>   | 130 to 420 lb max. |

| Compliant With: |                      |
|-----------------|----------------------|
| <b>OSHA</b>     | 1926.502 and 1910.66 |
| <b>ANSI</b>     | Z359.14-2021         |