

## 84711SG4

11' FT-X™ Web Class 1 SRL-P with Aluminum Snap Hook, Includes Aluminum Dorsal Connecting Carabiner

### Features :

- Dyneema® web lifeline provides ultimate durability with industry proven strength
- ViewPack® external energy absorber includes comprehensive fall clearance charts inside the cover
- Internal mechanism design minimizes unintentional lockups to keep you moving freely and productively
- Engineering housing material provides durability at low weight. Light green color denotes the non-leading edge capability of Class 1 SRLs
- Features aluminum snap hook leg-end connector
- Includes aluminum connecting carabiner
- Rated for workers weighing up to 420 pounds, including clothes, tools, gear, etc.
- May be anchored up to 5' below the dorsal D-ring with no edge hazards for user's weighing up to 310 lb max.
- Complies with ANSI Z359.14-2021 Class 1 SRL-P. [Learn more and download White Paper](#)

Material Specifications	
Webbing	Dyneema®; 4,500 lb min.
Energy Absorber	Polyester tear-away
Leg-End Connector	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength
Swivel Eye Connector	Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
Static Strength	3,600 lb min.
ANSI SRL Class/Type	Class 1 SRL-
Avg. Arrest Force	1,350 lb max.
Max. Arrest Force	1,800 lb
Max. Arrest Distance	42"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 420 lb max.

Compliant With:	
OSHA	1926.502 and 1910.66
ANSI	Z359.14-2021