



FS-FSP1420-W

Northstar Classic 20' Web SRL

*See chart for additional part numbers, hook configurations, and product weights

FEATURES :

- Swivel attachment point offers wide range of motion.
- High strength polymer housing resists impact.
- Heavy duty webbing includes fall indicator.
- Braking system activates quickly to arrest fall.
- All components are Z359.12 compliant.

Class
1
Anchor at or above dorsal D-ring



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66, 1926.502

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 41 in. (104 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	7 ft. 5 in. (2.3 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Webbing	25 mm UHMPE webbing
Housing	Nylon and glass fiber
Snap Hook	Zinc plated steel
Carabiner	Zinc plated steel



FS-FSP1420-W

Northstar Classic 20' Web SRL



Standards: ANSI Z359.14-2021
OSHA 1910.140, 1910.66 & 1926.502

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

		CONNECTOR										ATTACHMENT																					
Part Number	Single Leg (S) / Dual Leg (D) SRL Class	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	LI Steel Swivel Snap Hook ①	LI Steel Swivel Snap Hook ②	Dielectric Snap Hook ③	Steel Tie Back Hook ④	LI Steel Swivel Rebar Hook ⑤	Steel Swivel Rebar Hook ⑥	LI Steel Swivel Rebar Hook ⑦	Steel Swivel Rebar Hook ⑧	ALU Swivel Rebar Hook ⑨	ALU Swivel Eye Carabiner ⑩	ALU Swivel Carabiner ⑪	No Attachment ⑫	Trip Lock Steel Carabiner ⑬	ALU Captive Eye Carabiner ⑭	ALU Captive Eye Carabiner ⑮	ALU Snap Hook ⑯	F-S-EX313 ⑰	Gal Mount Bracket ⑱	Soft Loop ⑲	Integrated BWB ⑳	1014 BWB ㉑	9012 BWB ㉒	9013 BWB ㉓				
							FS-FSP1420-W	1 S	20	UHMPE Webbing	1X.05	Polymer	5.9	X												X							
FS-FSP1215-G	1 S	15	Steel Cable	ø3/16	Polymer	6.7		X											X														
FS-FSP1215-SS	1 S	15	S.S. Cable	ø3/16	Polymer	6.7		X											X														
FS-FSP1220-G	1 S	20	Steel Cable	ø3/16	Polymer	7.9		X											X														
FS-FSP1220-SS	1 S	20	S.S. Cable	ø3/16	Polymer	7.9		X											X														
FS-FSP1230-G	1 S	30	Steel Cable	ø3/16	Polymer	10.1		X											X														
FS-FSP1230-SS	1 S	30	S.S. Cable	ø3/16	Polymer	10.1		X											X														
FS-FSP1250-G	1 S	50	Steel Cable	ø3/16	Polymer	15.2		X											X														
FS-FSP1250-SS	1 S	50	S.S. Cable	ø3/16	Polymer	15.2		X											X														
FS-FSP1265-G	1 S	65	Steel Cable	ø3/16	Polymer	20.4		X											X														
FS-EX1080-G	1 S	80	Steel Cable	ø3/16	Polymer	27.4		X											X														
FS-EX10100-G	1 S	100	Steel Cable	ø3/16	Polymer	30.4		X											X														

