



## Latitude Edge 11' Cable SRL-P

\*See chart for part numbers, hook configurations, and product weights

### FEATURES :

- Unique protective shock pack cover with mesh lining for cool-air comfort.
- Convenient harness fastener straps for added security.
- Behind-the-web bracket attaches easily.
- Durable housing for added dependability.
- 360/180° attachment point swivels for full range of motion.
- Designed for sharp leading edges with foot-level connection.
- Single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Class  
**2**  
Anchor above or below dorsal D-ring

Product shown:  
SW8008-11LE-RBHDL

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 19 in. (48 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	5 ft. 7 in. (1.7 m)
For full clearance requirements, see user instructions	

ANSI CLASS 2	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 121 in. (307 cm)
Max. free fall distance	72 in. (152 cm)
Min. required fall clearance	17 ft. 1 in. (5.2 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Cable	3/16" galvanized steel
Bracket	Steel, aluminum (dependent on configuration)
Housing	Nylon
Hook options	Steel, aluminum, dielectric (dependent on configuration)
Shock pack	Polyester



## Latitude Edge 11' Cable SRL-P



Standards: ANSI Z359.14-2021  
OSHA 1910.140 & 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)  
OSHA Up to 420 lbs. (191kg)

Part Number	Single Leg (S) / Dual Leg (D)	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Hosing Material	Weight (lbs.)	CONNECTOR										ATTACHMENT																
							U-Steel Swivel Snap hook ①	Steel Snap hook ②	Dielectric Snap hook ③	Steel Tie Back hook ④	U-Steel Swivel Rear hook ⑤	Steel Swivel Rear hook ⑥	Steel Swivel Rear hook ⑦	Steel Captive Eye Carabiner ⑧	ALU Captive Eye Carabiner ⑨	ALU Swivel Carabiner ⑩	ALU Swivel Carabiner ⑪	No Attachment ⑫	Tip-Lock Steel Carabiner ⑬	Steel Carabiner ⑭	ALU Captive Eye Carabiner ⑮	ALU Carabiner ⑯	ALU Snap Hook ⑰	FS-E313 ⑱	Cap Mount Bracket ⑲	Integrated BWR ⑳	Soft Loop ㉑	1013 BWR ㉒	9012 BWR ㉓	9013 BWR ㉔			
SW8005-8LE	1, 2	S	8	Steel Cable	ø3/16	Nylon	5.1	X																									X
SW8005-8LE-ALU	1, 2	S	8	Steel Cable	ø3/16	Nylon	4.6			X																							X
SW8005-8LE-RBH	1, 2	S	8	Steel Cable	ø3/16	Nylon	5.6								X																	X	
SW8005-8LE-RBHALU	1, 2	S	8	Steel Cable	ø3/16	Nylon	5.4											X														X	
SW8005-8LE-DL	1, 2	D	8	Steel Cable	ø3/16	Nylon	9.1	X																								X	
SW8005-8LE-ALUDL	1, 2	D	8	Steel Cable	ø3/16	Nylon	8.5			X																						X	
SW8005-8LE-RBHDL	1, 2	D	8	Steel Cable	ø3/16	Nylon	10.5							X																		X	
SW8005-8LE-RBHALUDL	1, 2	D	8	Steel Cable	ø3/16	Nylon	10.1										X															X	
SW8008-11LE	1, 2	S	11	Steel Cable	ø3/16	Nylon	5.1	X																								X	
SW8008-11LE-ALU	1, 2	S	11	Steel Cable	ø3/16	Nylon	4.9			X																						X	
SW8008-11LE-RBH	1, 2	S	11	Steel Cable	ø3/16	Nylon	6.1								X																	X	
SW8008-11LE-RBHALU	1, 2	S	11	Steel Cable	ø3/16	Nylon	5.7											X														X	
SW8008-11LE-DL	1, 2	D	11	Steel Cable	ø3/16	Nylon	9.2	X																								X	
SW8008-11LE-ALUDL	1, 2	D	11	Steel Cable	ø3/16	Nylon	8.8			X																						X	
SW8008-11LE-RBHDL	1, 2	D	11	Steel Cable	ø3/16	Nylon	11.2								X																	X	
SW8008-11LE-RBHALUDL	1, 2	D	11	Steel Cable	ø3/16	Nylon	10.4										X															X	

